### Appendix E. R6 Stream Survey and PIBO Effectiveness Monitoring Data for the Murderers Creek Allotment

Table 1. Summary of Available R6 Stream Survey Data vs. Fish Habitat Standards for Streams within Allotments.

Bark Cabin, Tennessee, and Oregon Mine Creeks

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DC I		Data	PAC	💶   Amena 29 L	NMFS Matrix	of Pathways and anges of Criteria	l Indicators
(Italics) Both (Bold & Italics)	R6 Leve	el II Stream Surve	ey Data	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning
Stream Name	Bark Cabin Creek Reach 1	Tennessee Creek Reach 1	Oregon Mine Creek Reach 1	-	-	-	-	-
Pasture Name	Blue Ridge	Oregon Mine	Oregon Mine	-	-	-	-	-
Survey Date	1992 (June 27- June 29)	1995 (Aug 27- Sept 9)	1995 (Aug 22)	-	-	-	-	-
Sample Type	-	Riparian Only	Riparian Only	-	-	-	-	-
6 <sup>th</sup> Field HUC	170702010402	170702010301	170702010301	-	-	-	-	-
Av Bankfull (B) and/or Wetted (W) Width (feet)	B 3.0 W 2.4	W 3	-	-	-	-	-	-
Av Gradient (%)	4.0	5.3	6.6	-	-	-	-	-
Residual Pool Depth (feet)	0.3	-	-	-	-	-	-	-
Pool Frequency (#/mi)	37.08	-	-	96 <sup>2</sup> 56 <sup>3</sup> 47 <sup>4</sup> 26 <sup>5</sup>	75-132 <sup>2</sup> 38-66 <sup>3</sup> 30-53 <sup>4</sup> 15-26 <sup>5</sup>	Meets pool freq & LWD recruitment standards channel width # pools/mile 5 feet 184 10 " 96 15 " 70 20 " 56 25 " 47 50 " 26	Meets pool freq standards but not LWD recruitment	Does not meet pool freq standards

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DC L	LII Common Common	Data	PAC FISH	Amend 29	NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics) Both (Bold & Italics)	Ro Leve	el II Stream Surve	y Data	RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	
Pool Quality	No >1m deep pools, max spot temp 55.4F	Max spot temp 49.0F	Max spot temp 50.0F	-	-	Pools >1m (3.28ft) deep, good cover, cool water, minimal filling	Few >1m pools or inadequate cover/temp, moderate filling	No >1m pools & inadequate cover/temp, major filling with sediment	
Percent Pools	15.6	-	-	-	-	-	-	-	
Bankfull (B) or Wetted (W) W/D Ratio	B 5.0	B 11.7	B 12.6	<10 <sup>6</sup>	<10 <sup>6</sup>	<10 <sup>7</sup>	10-12 <sup>7</sup>	>12 <sup>7</sup>	
D50 (mm), or Dominant Substrate & Embeddedness	Sand, Embeddedness >35%	Gravel, Embeddedness <20%	Embeddednes s <20%	-	Embedded <=20%	Dominant substrate gravel (2-64 mm) or cobble (64-256 mm) (interstitial spaces clear), or embeddedness <20%	Gravel or cobble subdominant, or embeddedness 20-30% if dominant	Bedrock, sand, silt, or small gravel dominant, or embeddedness >30% if gravel or cobble dominant	
Pct Fines <2 mm in Riffles (R) or Pool Tails (P)	R 4.0	-	-	-	-	<12% fines <sup>8</sup> in gravel	12-20% fines <sup>8</sup> in gravel	>20% fines <sup>8</sup> in gravel	
Percent Stable Banks (CS & FB)	92.8	80-90	65-79	>80	>90	>90% stable	80-90% stable	< 80% stable	
Percent Stable Banks (CS, FB, US)	-	-	-	-	-	-	-	-	
Percent Undercut Banks	-	-	-	>75	50-75% undercut <sup>9</sup>	-	-	-	

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DC L	LII Com and Comme	Dota	PAC FISH	Amend 29	NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics) Both (Bold & Italics)		vel II Stream Survey Data			DFC	Properly Functioning	At Risk	Not Properly Functioning	
Large Wood Frequency (#/mi) <sup>14</sup>	23.4 <sup>10</sup> Potential recruitment is poor	-	-	>20 <sup>13</sup>	20-70 <sup>10</sup> 80-120 <sup>11</sup> 100-350 <sup>12</sup>	>20 <sup>13</sup> and adequate sources for recruitment	>20 but lacks recruitment to maintain	<20 and lacks recruitment	
Percent Shade/Canopy Closure	64.4	64.0	55.7	-	40-55 <sup>15</sup> 50-65 <sup>16</sup> 60-75 <sup>17</sup> 80 <sup>18</sup>	-	-	-	
Greenline Wetland Rating	-	-	-	-	-	-	-	-	
Greenline Woody Cover	-	-	-	-	-	-	-	-	
Physical Man-made Barriers <sup>19</sup>	none	None	Two barrier culverts	-	-	Any in watershed allow passage @ all flows	Any don't allow passage @ base flows	Any don't allow passage @ range of flows	
Off-channel Habitat & Refugia	0.3 percent side channels on reach	-	-	-	-	Low energy backwaters & side channels	Some backwaters & high energy side channels	Few or no backwaters	

Notes: 1) All PIBO data units converted from metric to English except for mm measurements; 2) Channels of <10 feet in width; 3) Channels of >10 to 20 feet in width; 4) Channels of >20 to 25 feet in width; 5) Channels of >25 to 50 feet in width; 6) Criteria is for wetted W/D ratio; 7) Criteria is for bankfull W/D ratio; 8) Fines defined as <0.85mm in gravel; 9) In non-forested systems with 2% or less gradient; 10) In Ponderosa pine ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 11) In mixed conifer ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 12) In Lodgepole pine ecosystems (at least 6 inches in diameter and 10% > 12 inches in diameter; and at least 18 feet long or 1.5 times bankfull width); 13) LWD defined as >12 inch diameter and > 35 ft length; 14) Stream surveys conducted in 1995 and earlier a) included not only LW material within the bankfull channel, but also leaning trees that have the potential to fall into the stream, and b) included a "Brush" LWD category that is not considered functional LWD as per Amendment 29 DFCs and the MPI unless in Lodgepole Pine ecosystems. Stream surveys conducted in 1996 and later a) only included trees actually within the bankfull channel interacting with stream flow during bankfull conditions, and

b) included a "Small" LWD category that is not considered functional LWD as described above; 15) In Ponderosa pine ecosystems; 16) In mixed conifer ecosystems; 17) In Lodgepole pine ecosystems; 18) In hardwood/meadow complexes; 19) Culvert barrier data from MNF Culvert Assessment GIS layer.

Table 2. Summary of Available R6 Stream Survey Data vs. Fish Habitat Standards for Streams within Allotments.

Buck, Vester, Blue, and Corral Creeks

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DC I	aval II Ctuan	- Cumusus Da	4.0	PAC	H Amena 29	NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics) Both (Bold & Italics)		evei ii Streai	m Survey Da	ta	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	
Stream Name	Buck Creek Reach 1	Vester Creek Reaches 1-2	Blue Creek Reach 1	Corral Creek Reaches 1-4	-	-	-	-	-	
Pasture Name	Frenchy Butte	Frenchy Butte	Frenchy Butte, Blue Ridge	Deer Creek	1	-	-	-	-	
Survey Date	1995 (July 31)	1995 (Aug 14-30)	1995 (Sept 7)	1993 (Aug 30-Sept 8)	-	-	-	-	-	
Sample Type	-	-	Riparian Only	-	-	-	-	-	-	
6 <sup>th</sup> Field HUC	1707020102 06	170702010 206	170702010 205	17070201 0206	-	-	-	-	-	
Av Bankfull (B) and/or Wetted (W) Width (feet)	B 4.6 W 4.1	B 4.1 W 3.9	W 2.1	B 6.1 W 5.1	-	-	-	-	-	
Av Gradient (%)	4.2	4.3	3.0	5.5	-	-	-	-	-	
Residual Pool Depth (feet)	0.8	0.9	-	1.0	-	-	-	-	-	
Pool Frequency	43.8	26.5	-	82.6	96 <sup>2</sup> 56 <sup>3</sup>	75-132 <sup>2</sup> 38-66 <sup>3</sup>	Meets pool freq & LWD recruitment standards	Meets pool freq standards but	Does not meet pool freq standards	

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DC.I	III C4ma an		1-	PAC FISH	Amend 29	NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics) Both (Bold & Italics)	R6 L	evei ii Strear	n Survey Da	ta	RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	
(#/mi)					47 <sup>4</sup> 26 <sup>5</sup>	30-53 <sup>4</sup> 15-26 <sup>5</sup>	channel width # pools/mile 5 feet 184 10 " 96 15 " 70 20 " 56 25 " 47 50 " 26	not LWD recruitment		
Pool Quality	Max spot temp 52.0F	Max spot temp 63.0F	Max spot temp 57.0F	0 >1m deep pools, Max spot temp 57.0F	-	-	Pools >1m (3.28ft) deep, good cover, cool water, minimal filling	Few >1m pools or inadequate cover/temp, moderate filling	No >1m pools & inadequate cover/temp, major filling with sediment	
Percent Pools	35.9	15.4	-	27.3	-	-	-	-	-	
Bankfull (B) or Wetted (W) W/D Ratio	B 10.3	B 8.7	B 12.1	B 7.0	<10 <sup>6</sup>	<10 <sup>6</sup>	<10 <sup>7</sup>	10-12 <sup>7</sup>	>12 <sup>7</sup>	
D50 (mm), or Dominant Substrate & Embeddedness	Gravel, Embeddedne ss <20%	Sand, Embedded ness >20%	Embedded ness <20%	Gravel, Embedde dness <30%	-	Embedded <=20%	Dominant substrate gravel (2-64 mm) or cobble (64-256 mm) (interstitial spaces clear), or embeddedness <20%	Gravel or cobble subdominant, or embeddedness 20-30% if dominant	Bedrock, sand, silt, or small gravel dominant, or embeddedness >30% if gravel or cobble dominant	
Pct Fines <2 mm in Riffles (R) or Pool Tails (P)	-	-	-	-	-		<12% fines <sup>8</sup> in gravel	12-20% fines <sup>8</sup> in gravel	>20% fines <sup>8</sup> in gravel	
Percent Stable	60.0	65-79	65-79	79.3	>80	>90	>90% stable	80-90% stable	< 80% stable	

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DC I	aval II Ctrass	··· Cumuau Da	40	FISH	Amend 29	NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics) Both (Bold & Italics)	K6 L	evel II Streal	m Survey Da	ta	RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	
Banks (CS & FB)										
Percent Stable Banks (CS, FB, US)	-	-	-	-	-	-	-	-	-	
Percent Undercut Banks	-	-	-	-	>75	50-75% undercut <sup>9</sup>	-	-	-	
Large Wood Frequency (#/mi) <sup>14</sup>	18.9 <sup>10</sup>	23.2 <sup>11</sup>	-	57.2 <sup>11</sup>	>20 <sup>13</sup>	20-70 <sup>10</sup> 80-120 <sup>11</sup> 100-350 <sup>12</sup>	>20 <sup>13</sup> and adequate sources for recruitment	>20 but lacks recruitment to maintain	<20 and lacks recruitment	
Percent Shade/Canopy Closure	54.0	51.0	28.0	43.0	-	40-55 <sup>15</sup> 50-65 <sup>16</sup> 60-75 <sup>17</sup> 80 <sup>18</sup>	-	-	-	
Greenline Wetland Rating	-	-	-	-	-	-	-	-	-	
Greenline Woody Cover	-	-	-	-	-	-	-	-	-	
Physical Man-made Barriers <sup>19</sup>	Two barrier culverts	None	None	Two barrier culverts	-	-	Any in watershed allow passage @ all flows	Any don't allow passage @ base flows	Any don't allow passage @ range of flows	
Off-channel Habitat & Refugia	-	-	-	-	-	-	Low energy backwaters & side channels	Some backwaters & high energy side channels	Few or no backwaters	

Notes: 1) All PIBO data units converted from metric to English except for mm measurements; 2) Channels of <10 feet in width; 3) Channels of >10 to 20 feet in width; 4) Channels of >20 to 25 feet in width; 5) Channels of >25 to 50 feet in width; 6) Criteria is for wetted W/D ratio; 7) Criteria is for bankfull W/D ratio; 8) Fines defined as <0.85mm in gravel; 9) In non-forested systems with 2% or less gradient; 10) In Ponderosa

pine ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 11) In mixed conifer ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 12) In Lodgepole pine ecosystems (at least 6 inches in diameter and 10% > 12 inches in diameter; and at least 18 feet long or 1.5 times bankfull width); 13) LWD defined as >12 inch diameter and > 35 ft length; 14) Stream surveys conducted in 1995 and earlier a) included not only LW material within the bankfull channel, but also leaning trees that have the potential to fall into the stream, and b) included a "Brush" LWD category that is not considered functional LWD as per Amendment 29 DFCs and the MPI unless in Lodgepole Pine ecosystems. Stream surveys conducted in 1996 and later a) only included trees actually within the bankfull channel interacting with stream flow during bankfull conditions, and b) included a "Small" LWD category that is not considered functional LWD as described above; 15) In Ponderosa pine ecosystems; 16) In mixed conifer ecosystems; 17) In Lodgepole pine ecosystems; 18) In hardwood/meadow complexes; 19) Culvert barrier data from MNF Culvert Assessment GIS layer.

Table 3. Summary of Available R6 Stream Survey and PIBO Data vs. Fish Habitat Standards for Streams within Allotments.

Crazy Creek

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	R6 Level	R6 Level II Stream		PIBO Effectiveness		Amend 29	NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics) Both (Bold & Italics)	Survey Data Monitoring Da		ing Data	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning		
Stream Name	Crazy Creek Reach 1	Crazy Creek Reach 1	Crazy Creek Reach 1	Crazy Creek Reach 1	-	-	-	-	-	
Pasture Name	Timber Mountain	Timber Mountain	Timber Mountain	Timber Mountain	-	-	-	-	-	
Survey Date	1992 (July 1-3)	2009 (July 7)	2003	2008	-	-	-	-	-	
Sample Type	-	-	К	К	-	-	-	-	-	
6 <sup>th</sup> Field HUC	170702010 402	<b>""</b>	6677	4477	-	-	-	-	-	
Av Bankfull (B) and/or Wetted (W) Width (feet)	W 4.9	W 5.3 B 13.6	-	-	-	-	-	-	-	
Av Gradient (%)	3.0	5.5	-	1	-	-	-	-	-	

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	R6 Level	II Stream	PIBO Effectiveness		PAC FISH	Amend 29	NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics) Both (Bold & Italics)	Surve	y Data	Monitori	ing Data	RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	
Residual Pool Depth (feet)	0.6	0.8	-	0.16	-	-	-	-	-	
Pool Frequency (#/mi)	121.48	75.0	-	-	96 <sup>2</sup> 56 <sup>3</sup> 47 <sup>4</sup> 26 <sup>5</sup>	75-132 <sup>2</sup> 38-66 <sup>3</sup> 30-53 <sup>4</sup> 15-26 <sup>5</sup>	Meets pool freq & LWD recruitment standards channel width # pools/mile 5 feet 184 10 " 96 15 " 70 20 " 56 25 " 47 50 " 26	Meets pool freq standards but not LWD recruitment	Does not meet pool freq standards	
Pool Quality	No >1m deep pools, max spot temp 57.2F	No >1m deep pools, max spot temp 60.8 F	-	-	-	-	Pools >1m (3.28ft) deep, good cover, cool water, minimal filling	Few >1m pools or inadequate cover/temp, moderate filling	No >1m pools & inadequate cover/temp, major filling with sediment	
Percent Pools	43.3	27.6	-	31.7	-	-	-	-	-	
Bankfull (B) or Wetted (W) W/D Ratio	B 10.9	B 13.6	-	B 32.9	<10 <sup>6</sup>	<10 <sup>6</sup>	<10 <sup>7</sup>	10-12 <sup>7</sup>	>12 <sup>7</sup>	
D50 (mm), or Dominant Substrate & Embeddedness	Gravel, Embedded ness >35%	15.0	-	-	-	Embedded <=20%	Dominant substrate gravel (2-64 mm) or cobble (64-256 mm) (interstitial spaces clear), or embeddedness <20%	Gravel or cobble subdominant, or embeddedness 20-30% if dominant	Bedrock, sand, silt, or small gravel dominant, or embeddedness >30% if gravel or cobble dominant	
Pct Fines <2 mm in Riffles (R) or Pool	-	-	-	-	-	-	<12% fines <sup>8</sup> in gravel	12-20% fines <sup>8</sup> in gravel	>20% fines <sup>8</sup> in gravel	

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	R6 Level	II Stream	PIBO Effe	ctiveness	PAC FISH	Amend 29		of Pathways and anges of Criteria	Indicators
(Italics) Both (Bold & Italics)	Surve	y Data	Monitori	ing Data	RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning
Tails (P)									
Percent Stable Banks (CS & FB)	97.0	98.5	83.3	88.1	>80	>90	>90% stable	80-90% stable	< 80% stable
Percent Stable Banks (CS, FB, US)	-	-	-	-	-	-	-	-	-
Percent Undercut Banks	-	-	14.3	7.3	>75	50-75% undercut <sup>9</sup>	-	-	-
Large Wood Frequency (#/mi) <sup>14</sup>	22.0 <sup>11</sup> , Poor Recruitmen t	6.3 <sup>11</sup> , Poor Recruitmen t	1	-	>20 <sup>13</sup>	20-70 <sup>10</sup> 80-120 <sup>11</sup> 100-350 <sup>12</sup>	>20 <sup>13</sup> and adequate sources for recruitment	>20 but lacks recruitment to maintain	<20 and lacks recruitment
Percent Shade/Canopy Closure	69	-	-	-	-	40-55 <sup>15</sup> 50-65 <sup>16</sup> 60-75 <sup>17</sup> 80 <sup>18</sup>	-	-	-
Greenline Wetland Rating	-	-	57.2	59.8	_	-	-	-	-
Greenline Woody Cover	-	-	84.9	69.9	-	-	-	-	-
Physical Man-made Barriers <sup>19</sup>	None	None	-	-	-	-	Any in watershed allow passage @ all flows	Any don't allow passage @ base flows	Any don't allow passage @ range of flows
Off-channel Habitat & Refugia	Side channels on 3.2% of reach	Side channels on 1.41% of reach	-	-	-	-	Low energy backwaters & side channels	Some backwaters & high energy side channels	Few or no backwaters

Notes: 1) All PIBO data units converted from metric to English except for mm measurements; 2) Channels of <10 feet in width; 3) Channels of >10 to 20 feet in width; 4) Channels of >20 to 25 feet in width; 5) Channels of >25 to 50 feet in width; 6) Criteria is for wetted W/D ratio; 7) Criteria is for bankfull W/D ratio; 8) Fines defined as <0.85mm in gravel; 9) In non-forested systems with 2% or less gradient; 10) In Ponderosa pine ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 11) In mixed conifer ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 12) In Lodgepole pine ecosystems (at least 6 inches in diameter and 10% > 12 inches in diameter; and at least 18 feet long or 1.5 times bankfull width); 13) LWD defined as >12 inch diameter and > 35 ft length; 14) Stream surveys conducted in 1995 and earlier a) included not only LW material within the bankfull channel, but also leaning trees that have the potential to fall into the stream, and b) included a "Brush" LWD category that is not considered functional LWD as per Amendment 29 DFCs and the MPI unless in Lodgepole Pine ecosystems. Stream surveys conducted in 1996 and later a) only included trees actually within the bankfull channel interacting with stream flow during bankfull conditions, and b) included a "Small" LWD category that is not considered functional LWD as described above; 15) In Ponderosa pine ecosystems; 16) In mixed conifer ecosystems; 17) In Lodgepole pine ecosystems; 18) In hardwood/meadow complexes; 19) Culvert barrier data from MNF Culvert Assessment GIS layer.

Table 4. Summary of Available R6 Stream Survey Data vs. Fish Habitat Standards for Streams within Allotments.

Deer Creek

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	De	R6 Level II Stream Survey Data					NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics) Both (Bold & Italics)		Level II Strea	im Survey Da	ata	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	
Stream Name	Deer Creek Reaches 1- 10	Deer Creek Reaches 1- 4	Deer Creek Reaches 11-13	Deer Creek Reach 5	-	-	-	-	-	
Pasture Name	Frenchy Butte	Frenchy Butte	Deer Creek	Deer Creek	-	-	-	-	-	
Survey Date	1991 (July 27)	2007 (July 30-Aug 2)	1991 (Jul 27)	2007 (Jul 30-Aug 2)	-	-	-	-	-	
Sample Type	-	-	-	-	-	-	-	-	-	
6 <sup>th</sup> Field HUC	170702010 206	170702010 206	170702010 205	170702010 205	-	-	-	-	-	
Av Bankfull (B) and/or Wetted (W)	B 18.8 W 13.6	W 7.6	W 9.4	W 6.5	-	-	-	-	-	

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DC	Lavel II Ctra	om Comoo D	-10	PAC FISH	H   Amena 29	NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics) Both (Bold & Italics)		Level II Strea	im Survey D	ata	RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	
Width (feet)										
Av Gradient (%)	1.5	1.6	1.0	1.6	-	-	-	-	-	
Residual Pool Depth (feet)	1.7	1.7	1.4	1.6	-	-	-	-	-	
Pool Frequency (#/mi)	36.1	26.2	37.9	26.3	96 <sup>2</sup> 56 <sup>3</sup> 47 <sup>4</sup> 26 <sup>5</sup>	75-132 <sup>2</sup> 38-66 <sup>3</sup> 30-53 <sup>4</sup> 15-26 <sup>5</sup>	Meets pool freq & LWD recruitment standards channel width # pools/mile 5 feet 184 10 " 96 15 " 70 20 " 56 25 " 47 50 " 26	Meets pool freq standards but not LWD recruitment	Does not meet pool freq standards	
Pool Quality	10 >1m deep pools, Max spot temp 59F	2 >1m deep pools, Max spot temp 59F	1 >1m deep pool, Max spot temp 59F	No >1m deep pools, Max spot temp 57F	-	-	Pools >1m (3.28ft) deep, good cover, cool water, minimal filling	Few >1m pools or inadequate cover/temp, moderate filling	No >1m pools & inadequate cover/temp, major filling with sediment	
Percent Pools	28.54	-	31.17	-	-	-	-	-	-	
Bankfull (B) or Wetted (W) W/D Ratio	B 16.4	B15.7	-	B12.7	<10 <sup>6</sup>	<10 <sup>6</sup>	<10 <sup>7</sup>	10-12 <sup>7</sup>	>12 <sup>7</sup>	
D50 (mm), or Dominant Substrate & Embeddedness	Cobble, Embedded ness >35%	Gravel, Embedded ness >35%	Cobble, Embedded ness >35%	Gravel, Embedded ness not >35%	-	Embedded <=20%	Dominant substrate gravel (2-64 mm) or cobble (64-256 mm) (interstitial spaces clear), or	Gravel or cobble subdominant, or embeddedness 20-30% if dominant	Bedrock, sand, silt, or small gravel dominant, or embeddedness >30% if gravel or	

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	D.C.	Laval II Ctass	C	-4-	PAC FISH	Amend 29	NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics) Both (Bold & Italics)		Level II Stream	am Survey Da	ata	RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	
							embeddedness <20%		cobble dominant	
Pct Fines <2 mm in Riffles (R) or Pool Tails (P)	-	-	-	-	-	-	<12% fines <sup>8</sup> in gravel	12-20% fines <sup>8</sup> in gravel	>20% fines <sup>8</sup> in gravel	
Percent Stable Banks (CS & FB)	-	96.0	-	96.0	>80	>90	>90% stable	80-90% stable	< 80% stable	
Percent Stable Banks (CS, FB, US)	-	-	-	-	-	-	-	-	-	
Percent Undercut Banks	-	-	-	-	>75	50-75% undercut <sup>9</sup>	-	-	-	
Large Wood Frequency (#/mi) <sup>14</sup>	55 <sup>10</sup> , Poor Recruitmen t	27 <sup>10</sup>	34 <sup>10</sup> , Poor Recruitmen t	48 <sup>10</sup>	>20 <sup>13</sup>	20-70 <sup>10</sup> 80-120 <sup>11</sup> 100-350 <sup>12</sup>	>20 <sup>13</sup> and adequate sources for recruitment	>20 but lacks recruitment to maintain	<20 and lacks recruitment	
Percent Shade/Canopy Closure	-	48.8	-	44.0	-	40-55 <sup>15</sup> 50-65 <sup>16</sup> 60-75 <sup>17</sup> 80 <sup>18</sup>	-	-	-	
Greenline Wetland Rating	-	-	-	-	-	-	-	-	-	
Greenline Woody Cover	-	-	-	-	-	-	-	-	-	
Physical Man-made Barriers <sup>19</sup>	4 culvert barriers	4 culvert barriers	3 culvert barriers	3 culvert barriers	-	-	Any in watershed allow passage @ all flows	Any don't allow passage @ base flows	Any don't allow passage @ range of flows	

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol (Italics)	R6 Level II Stream Survey Data					Amend 29	NMFS Matrix of Pathways and Indicators Ranges of Criteria			
Both (Bold & Italics)		Level II Strea	im Survey Da	ata	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	
Off-channel Habitat & Refugia	-	Side channels on 0.9% of reaches	-	Side channels on 0.4% of reach	-	-	Low energy backwaters & side channels	Some backwaters & high energy side channels	Few or no backwaters	

Notes: 1) All PIBO data units converted from metric to English except for mm measurements; 2) Channels of <10 feet in width; 3) Channels of >10 to 20 feet in width; 4) Channels of >20 to 25 feet in width; 5) Channels of >25 to 50 feet in width; 6) Criteria is for wetted W/D ratio; 7) Criteria is for bankfull W/D ratio; 8) Fines defined as <0.85mm in gravel; 9) In non-forested systems with 2% or less gradient; 10) In Ponderosa pine ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 11) In mixed conifer ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 12) In Lodgepole pine ecosystems (at least 6 inches in diameter and 10% > 12 inches in diameter; and at least 18 feet long or 1.5 times bankfull width); 13) LWD defined as >12 inch diameter and > 35 ft length; 14) Stream surveys conducted in 1995 and earlier a) included not only LW material within the bankfull channel, but also leaning trees that have the potential to fall into the stream, and b) included a "Brush" LWD category that is not considered functional LWD as per Amendment 29 DFCs and the MPI unless in Lodgepole Pine ecosystems. Stream surveys conducted in 1996 and later a) only included trees actually within the bankfull channel interacting with stream flow during bankfull conditions, and b) included a "Small" LWD category that is not considered functional LWD as described above; 15) In Ponderosa pine ecosystems; 16) In mixed conifer ecosystems; 17) In Lodgepole pine ecosystems; 18) In hardwood/meadow complexes; 19) Culvert barrier data from MNF Culvert Assessment GIS layer.

Table 5. Summary of Available R6 Stream Survey Data vs. Fish Habitat Standards for Streams within Allotments.

Duncan Creek

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol (Italics)	R6 Level II Stream Survey Data				Amend 29		x of Pathways and Indicators Ranges of Criteria		
Both (Bold & Italics)		Stream Surve	ey Data	FISH RMO	DFC Properly Functioning		At Risk	Not Properly Functioning	
Stream Name	Duncan Creek Reach 1					-	-	-	
Pasture Name	Martin Corrals	Corrals Red Rocks Oregon Mine			-	-		-	

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DO LOUGHI	04	Parts	PAC	Amend 29		of Pathways and Indicators anges of Criteria		
(Italics) Both (Bold & Italics)	R6 Level II	Stream Surve	y Data	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	
Survey Date	1994 (Sept 14-28)	1994 (Sept 14-28)	1994 (Sept 14- 28)	-	-	-	-	-	
Sample Type	-	-	-	-	-	-	-	-	
6 <sup>th</sup> Field HUC	170702010303	427	4279	-	-	-	-	-	
Av Bankfull (B) and/or Wetted (W) Width (feet)	B 13.9 W 8.6	B 12.7 W 6.8	B 14.1 W 4.3	-	-	-	-	-	
Av Gradient (%)	5.0	4.7	7.0	-	-	-	-	-	
Residual Pool Depth (feet)	0.9	0.8	0.6	-	-	-	-	-	
Pool Frequency (#/mi)	36.5	31.0	31.9	96 <sup>2</sup> 56 <sup>3</sup> 47 <sup>4</sup> 26 <sup>5</sup>	75-132 <sup>2</sup> 38-66 <sup>3</sup> 30-53 <sup>4</sup> 15-26 <sup>5</sup>	Meets pool freq & LWD recruitment standards channel width # pools/mile 5 feet 184 10 " 96 15 " 70 20 " 56 25 " 47 50 " 26	Meets pool freq standards but not LWD recruitment	Does not meet pool freq standards	
Pool Quality	0 >1m deep pools, max spot temp 52.0F	0 >1m deep pools, max spot temp 52.0F	0 >1m deep pools, max spot temp 52.0F		-	Pools >1m (3.28ft) deep, good cover, cool water, minimal filling	Few >1m pools or inadequate cover/temp, moderate filling	No >1m pools & inadequate cover/temp, major filling with sediment	
Percent Pools	16.4	11.9	8.4	-	-	-	-	-	
Bankfull (B) or Wetted (W) W/D	B 6.0	B 5.6	B 7.9	<10 <sup>6</sup>	<10 <sup>6</sup>	<10 <sup>7</sup>	10-12 <sup>7</sup>	>12 <sup>7</sup>	

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	P01	04	Data	PAC	Amend 29		of Pathways and anges of Criteria	I Indicators
(Italics) Both (Bold & Italics)	K6 Level II	Stream Surve	y Data	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning
Ratio								
D50 (mm), or Dominant Substrate & Embeddedness	Gravel, Embeddedness >35%	Gravel, Embeddedn ess >35%	Gravel, Embeddednes s >35%	-	Embedded <=20%	Dominant substrate gravel (2-64 mm) or cobble (64-256 mm) (interstitial spaces clear), or embeddedness <20%	Gravel or cobble subdominant, or embeddedness 20-30% if dominant	Bedrock, sand, silt, or small gravel dominant, or embeddedness >30% if gravel or cobble dominant
Pct Fines <2 mm in Riffles (R) or Pool Tails (P)	-	-	-	-	-	<12% fines <sup>8</sup> in gravel	12-20% fines <sup>8</sup> in gravel	>20% fines <sup>8</sup> in gravel
Percent Stable Banks (CS & FB)	83.0	92.7	100.0	>80	>90	>90% stable	80-90% stable	< 80% stable
Percent Stable Banks (CS, FB, US)	-	-	-	-	-	-	-	-
Percent Undercut Banks	-	-	-	>75	50-75% undercut <sup>9</sup>	-	-	-
Large Wood Frequency (#/mi) <sup>14</sup>	45.0 <sup>11</sup> Good Recruitment	87.3 <sup>11</sup> Fair Recruitment	114.8 <sup>11</sup> Low Recruitment	>20 <sup>13</sup>	20-70 <sup>10</sup> 80-120 <sup>11</sup> 100-350 <sup>12</sup>	>20 <sup>13</sup> and adequate sources for recruitment	>20 but lacks recruitment to maintain	<20 and lacks recruitment
Percent Shade/Canopy Closure	> 60.0	> 60.0	> 60.0	-	40-55 <sup>15</sup> 50-65 <sup>16</sup> 60-75 <sup>17</sup> 80 <sup>18</sup>	-	-	-
Greenline Wetland Rating	-	-	-	-	-	-	-	-

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol (Italics)	DC Lavel III	R6 Level II Stream Survey Data				NMFS Matrix of Pathways and Indicators Ranges of Criteria			
Both (Bold & Italics)		Stream Surve	ey Data	FISH Amend 29 L		Properly Functioning	At Risk	Not Properly Functioning	
Greenline Woody Cover	-	-	-	-	-	-	-	-	
Physical Man-made Barriers <sup>19</sup>	None	None	One barrier culvert	-	-	Any in watershed allow passage @ all flows	Any don't allow passage @ base flows	Any don't allow passage @ range of flows	
Off-channel Habitat & Refugia	17 side channels, 6% of reach	76 side channels, average 4.5% of reaches	50 side channels, average <4% of reaches	-	-	Low energy backwaters & side channels	Some backwaters & high energy side channels	Few or no backwaters	

Notes: 1) All PIBO data units converted from metric to English except for mm measurements; 2) Channels of <10 feet in width; 3) Channels of >10 to 20 feet in width; 4) Channels of >20 to 25 feet in width; 5) Channels of >25 to 50 feet in width; 6) Criteria is for wetted W/D ratio; 7) Criteria is for bankfull W/D ratio; 8) Fines defined as <0.85mm in gravel; 9) In non-forested systems with 2% or less gradient; 10) In Ponderosa pine ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 11) In mixed conifer ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 12) In Lodgepole pine ecosystems (at least 6 inches in diameter and 10% > 12 inches in diameter; and at least 18 feet long or 1.5 times bankfull width); 13) LWD defined as >12 inch diameter and > 35 ft length; 14) Stream surveys conducted in 1995 and earlier a) included not only LW material within the bankfull channel, but also leaning trees that have the potential to fall into the stream, and b) included a "Brush" LWD category that is not considered functional LWD as per Amendment 29 DFCs and the MPI unless in Lodgepole Pine ecosystems. Stream surveys conducted in 1996 and later a) only included trees actually within the bankfull channel interacting with stream flow during bankfull conditions, and b) included a "Small" LWD category that is not considered functional LWD as described above; 15) In Ponderosa pine ecosystems; 16) In mixed conifer ecosystems; 17) In Lodgepole pine ecosystems; 18) In hardwood/meadow complexes; 19) Culvert barrier data from MNF Culvert Assessment GIS layer.

Table 6. Summary of Available R6 Stream Survey Data vs. Fish Habitat Standards for Streams within Allotments.

East and West Tributaries Duncan Creek

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	P6 Lovel II Stroam Survey Data	PAC	Amend 29	NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics)  Both (Bold & Italics)	R6 Level II Stream Survey Data	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DO Lavral III Otra	am Comos Data	PAC	Amend 29	runctioning		
(Italics) Both (Bold & Italics)	R6 Level II Stre	am Survey Data	FISH RMO	DFC	Properly Functioning	At Risk	
Stream Name	East Tributary Duncan Creek Reach 1	West Tributary Duncan Creek Reach 1	-	-	-	-	-
Pasture Name	Red Rocks, Oregon Mine	Oregon Mine	-	-	-	-	-
Survey Date	1994 (Sept 23)	1994 (Sept 30)	-	-	-	-	-
Sample Type	-	-	-	-	-	-	-
6 <sup>th</sup> Field HUC	170702010303	433	-	-	-	-	-
Av Bankfull (B) and/or Wetted (W) Width (feet)	B 10.0 W 3.4	B 15.0 W 3.0	-	-	-	-	-
Av Gradient (%)	10.0	10.0	-	-	-	-	-
Residual Pool Depth (feet)	0.6	0.4	-	-	-	-	-
Pool Frequency (#/mi)	28.9	31.6	96 <sup>2</sup> 56 <sup>3</sup> 47 <sup>4</sup> 26 <sup>5</sup>	75-132 <sup>2</sup> 38-66 <sup>3</sup> 30-53 <sup>4</sup> 15-26 <sup>5</sup>	5 feet 184 10 " 96 15 " 70	standards but not LWD	
Pool Quality	0 >1m deep pools, max spot temp 54.0F	0 >1m deep pools		-	Pools >1m (3.28ft) deep, good cover, cool water, minimal filling	Few >1m pools or inadequate cover/temp, moderate filling	No >1m pools & inadequate cover/temp, major filling with sediment

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DOI 1110	0 0.	PAC	Amand 20		of Pathways and anges of Criteria	I Indicators
(Italics) Both (Bold & Italics)	Ro Levei II Stre	am Survey Data	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning
Percent Pools	5.9	4.1	-	-	-	-	-
Bankfull (B) or Wetted (W) W/D Ratio	B 5.0	B 10.0	<10 <sup>6</sup>	<10 <sup>6</sup>	<10 <sup>7</sup>	10-12 <sup>7</sup>	>12 <sup>7</sup>
D50 (mm), or Dominant Substrate & Embeddedness	Gravel, Embeddedness >35%	Gravel, Embeddedness >35%	-	Embedded <=20%	Dominant substrate gravel (2-64 mm) or cobble (64-256 mm) (interstitial spaces clear), or embeddedness <20%	Gravel or cobble subdominant, or embeddedness 20-30% if dominant	Bedrock, sand, silt, or small gravel dominant, or embeddedness >30% if gravel or cobble dominant
Pct Fines <2 mm in Riffles (R) or Pool Tails (P)	-	-	-	-	<12% fines <sup>8</sup> in gravel	12-20% fines <sup>8</sup> in gravel	>20% fines <sup>8</sup> in gravel
Percent Stable Banks (CS & FB)	56.0	67.0	>80	>90	>90% stable	80-90% stable	< 80% stable
Percent Stable Banks (CS, FB, US)	-	-	-	-	-	-	-
Percent Undercut Banks	-	-	>75	50-75% undercut <sup>9</sup>	-	-	-
Large Wood Frequency (#/mi) <sup>14</sup>	64.9 <sup>11</sup>	117.7 <sup>11</sup>	>20 <sup>13</sup>	20-70 <sup>10</sup> 80-120 <sup>11</sup> 100-350 <sup>12</sup>	>20 <sup>13</sup> and adequate sources for recruitment	>20 but lacks recruitment to maintain	<20 and lacks recruitment
Percent Shade/Canopy Closure	> 60.0	> 60.0	-	40-55 <sup>15</sup> 50-65 <sup>16</sup> 60-75 <sup>17</sup>	-	-	-

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DO Lavel II Otro	R6 Level II Stream Survey Data		Amend 29		of Pathways and Indicators anges of Criteria  At Risk  Not Properly Functioning  -  -  Any don't allow passage @ base flows  Some backwaters & high energy side channels  Few or no backwaters backwaters high energy side channels	
(Italics) Both (Bold & Italics)	Ro Level II Stre	am Survey Data	FISH RMO	DFC	Properly Functioning	At Risk	
				80 <sup>18</sup>			
One on line Westlemal							
Greenline Wetland Rating	-	-		-	-	-	-
Greenline Woody Cover	-	-	-	-	-	-	-
Physical Man-made Barriers <sup>19</sup>	None	One barrier culvert	-	-	Any in watershed allow passage @ all flows	passage @	passage @ range of
Off-channel Habitat & Refugia	4 side channels	1 side channel	-	-	Low energy backwaters & side channels	backwaters &	

Notes: 1) All PIBO data units converted from metric to English except for mm measurements; 2) Channels of <10 feet in width; 3) Channels of >10 to 20 feet in width; 4) Channels of >20 to 25 feet in width; 5) Channels of >25 to 50 feet in width; 6) Criteria is for wetted W/D ratio; 7) Criteria is for bankfull W/D ratio; 8) Fines defined as <0.85mm in gravel; 9) In non-forested systems with 2% or less gradient; 10) In Ponderosa pine ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 11) In mixed conifer ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 12) In Lodgepole pine ecosystems (at least 6 inches in diameter and 10% > 12 inches in diameter; and at least 18 feet long or 1.5 times bankfull width); 13) LWD defined as >12 inch diameter and > 35 ft length; 14) Stream surveys conducted in 1995 and earlier a) included not only LW material within the bankfull channel, but also leaning trees that have the potential to fall into the stream, and b) included a "Brush" LWD category that is not considered functional LWD as per Amendment 29 DFCs and the MPI unless in Lodgepole Pine ecosystems. Stream surveys conducted in 1996 and later a) only included trees actually within the bankfull channel interacting with stream flow during bankfull conditions, and b) included a "Small" LWD category that is not considered functional LWD as described above; 15) In Ponderosa pine ecosystems; 16) In mixed conifer ecosystems; 17) In Lodgepole pine ecosystems; 18) In hardwood/meadow complexes; 19) Culvert barrier data from MNF Culvert Assessment GIS layer.

Table 7. Summary of Available R6 Stream Survey Data vs. Fish Habitat Standards for Streams within Allotments.

Murderers Creek 1992

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DC L ···	!!! С	C	4.5	PAC FISH	Amend 29		of Pathways and anges of Criteria	Indicators
(Italics) Both (Bold & Italics)		vel II Stream	Survey Da	та	RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning
Stream Name	Murderers Cr Reaches 1-2	Murderer s Cr Reaches 2-6	Murderer s Cr Reaches 6-8	Murderer s Cr Reaches 8-9	-	-	-	-	-
Pasture Name	Martin Corrals	Oregon Mine	Tex Cr Gather	Murderers Cr Gather	1	-	-	-	-
Survey Date	1992 (June 24- July 8)	1992 (June 24- July 8)	1992 (June 24- July 8)	1992 (June 24- July 8)	1	1	-	-	-
Sample Type	-	-	-	-	-	-	-	-	-
6 <sup>th</sup> Field HUC	170702010301		,	4477	-	-	-	-	-
Av Bankfull (B) and/or Wetted (W) Width (feet)	W 15.0	W 13.2	W 9.5	W 8.5	-	-	-	-	-
Av Gradient (%)	4.0	3.0	4.3	3.0	-	-	-	-	-
Residual Pool Depth (feet)	1.5	1.5	1.7	1.6	1	-	-	-	-
Pool Frequency (#/mi)	37.3	34.0	29.6	38.0	96 <sup>2</sup> 56 <sup>3</sup> 47 <sup>4</sup> 26 <sup>5</sup>	75-132 <sup>2</sup> 38-66 <sup>3</sup> 30-53 <sup>4</sup> 15-26 <sup>5</sup>	Meets pool freq & LWD recruitment standards channel width # pools/mile 5 feet 184 10 " 96 15 " 70 20 " 56 25 " 47 50 " 26	Meets pool freq standards but not LWD recruitment	Does not meet pool freq standards

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DC L ···	! II Ct	. C	4-	PAC	Amend 29		of Pathways and anges of Criteria	of Pathways and Indicators anges of Criteria	
(Italics) Both (Bold & Italics)	R6 Lev	el II Stream	i Survey Da	та	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	
Pool Quality	Max spot temp 64.4F	Max spot temp 68.0F	Max spot temp 62.6F	Max spot temp 69.8F	-	-	Pools >1m (3.28ft) deep, good cover, cool water, minimal filling	Few >1m pools or inadequate cover/temp, moderate filling	No >1m pools & inadequate cover/temp, major filling with sediment	
Percent Pools	25.5	51.5	76.2	74.9	-	-	-	-	-	
Bankfull (B) or Wetted (W) W/D Ratio	B 9.2	B 15.3	B 14.5	B 12.1	<10 <sup>6</sup>	<10 <sup>6</sup>	<10 <sup>7</sup>	10-12 <sup>7</sup>	>12 <sup>7</sup>	
D50 (mm), or Dominant Substrate & Embeddedness	Cobble. > 35% Embedded.	Cobble. > 35% Embedde d.	Sand. > 35% Embedde d.	Sand. > 35% Embedde d.	-	Embedded <=20%	Dominant substrate gravel (2-64 mm) or cobble (64-256 mm) (interstitial spaces clear), or embeddedness <20%	Gravel or cobble subdominant, or embeddedness 20-30% if dominant	Bedrock, sand, silt, or small gravel dominant, or embeddedness >30% if gravel or cobble dominant	
Pct Fines <2 mm in Riffles (R) or Pool Tails (P)	-	-	-	-	-	-	<12% fines <sup>8</sup> in gravel	12-20% fines <sup>8</sup> in gravel	>20% fines <sup>8</sup> in gravel	
Percent Stable Banks (CS & FB)	-	-	98	-	>80	>90	>90% stable	80-90% stable	< 80% stable	
Percent Stable Banks (CS, FB, US)	-	-	-	-	-	-	-	-	-	
Percent Undercut Banks	-	-	-	-	>75	50-75% undercut <sup>9</sup>	-	-	-	

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DC L ov	val II Ctuanus	Suman Da	4-	PAC	Amend 29		latrix of Pathways and Indicators Ranges of Criteria		
(Italics) Both (Bold & Italics)	Ko Lev	el II Stream	i Survey Da	та	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	
Large Wood Frequency (#/mi) <sup>14</sup>	77.6 <sup>10</sup> , low recruitment	29.4 <sup>10</sup> , low recruitme nt	19.6 <sup>10</sup> , low recruitme nt	46.9 <sup>10</sup> , low recruitme nt	>20 <sup>13</sup>	20-70 <sup>10</sup> 80-120 <sup>11</sup> 100-350 <sup>12</sup>	>20 <sup>13</sup> and adequate sources for recruitment	>20 but lacks recruitment to maintain	<20 and lacks recruitment	
Percent Shade/Canopy Closure	81.5	50.8	40	40	-	40-55 <sup>15</sup> 50-65 <sup>16</sup> 60-75 <sup>17</sup> 80 <sup>18</sup>	-	-	-	
Greenline Wetland Rating	-	-	-	-	-	-	-	-	-	
Greenline Woody Cover	-	-	-	-	-	-	-	-	-	
Physical Man-made Barriers <sup>19</sup>	None	2 Barrier Culverts (Reach 6)	2 Barrier Culverts (Reach 6)	1 Barrier Culvert (Reach 9)	-	-	Any in watershed allow passage @ all flows	Any don't allow passage @ base flows	Any don't allow passage @ range of flows	
Off-channel Habitat & Refugia	Side channels on 2.0% of reaches	Side channels on 2.8% of reaches, beaver ponds	Side channels on 3.9% of reaches, beaver ponds	Side channels on 1.6% of reaches, beaver ponds	-	-	Low energy backwaters & side channels	Some backwaters & high energy side channels	Few or no backwaters	

Notes: 1) All PIBO data units converted from metric to English except for mm measurements; 2) Channels of <10 feet in width; 3) Channels of >10 to 20 feet in width; 4) Channels of >20 to 25 feet in width; 5) Channels of >25 to 50 feet in width; 6) Criteria is for wetted W/D ratio; 7) Criteria is for bankfull W/D ratio; 8) Fines defined as <0.85mm in gravel; 9) In non-forested systems with 2% or less gradient; 10) In Ponderosa pine ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 11) In mixed conifer ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 12) In Lodgepole pine ecosystems (at least 6 inches in diameter and 10% > 12 inches in diameter; and at least 18 feet long or 1.5 times bankfull width); 13) LWD defined as >12 inch diameter and > 35 ft length; 14) Stream surveys conducted in 1995 and earlier a) included not only LW

material within the bankfull channel, but also leaning trees that have the potential to fall into the stream, and **b**) included a "Brush" LWD category that is not considered functional LWD as per Amendment 29 DFCs and the MPI unless in Lodgepole Pine ecosystems. Stream surveys conducted in 1996 and later **a**) only included trees actually within the bankfull channel interacting with stream flow during bankfull conditions, and **b**) included a "Small" LWD category that is not considered functional LWD as described above; **15**) In Ponderosa pine ecosystems; **16**) In mixed conifer ecosystems; **17**) In Lodgepole pine ecosystems; **18**) In hardwood/meadow complexes; **19**) Culvert barrier data from MNF Culvert Assessment GIS layer.

Table 8. Summary of Available R6 Stream Survey Data vs. Fish Habitat Standards for Streams within Allotments.

Murderers Creek 2005

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DC Lavel II Ctree	m Cumusu Data	PAC Amend 29			of Pathways and anges of Criteria	
(Italics) Both (Bold & Italics)	R6 Level II Strea	im Survey Data	RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning
Stream Name	Murderers Cr Reach 1	Murderers Cr Reach 2	-	-	-	-	-
Pasture Name	Martin Corrals, Oregon Mine	Tex Cr Gather, Murderers Cr Gather	-	-	-	-	-
Survey Date	2005 (July 18-29)	2005 (July 18-29)	-	-	-	-	-
Sample Type	-	-	-	-	-	-	-
6 <sup>th</sup> Field HUC	170702010301	6633	-	-	-	-	-
Av Bankfull (B) and/or Wetted (W) Width (feet)	W 15.0 B 18.6	W 14.0 B17.5	-	-	-	-	-
Av Gradient (%)	3.2	1.1	-	-	-	-	-
Residual Pool Depth (feet)	1.8	1.7	-	-	-	-	-
Pool Frequency (#/mi)	21.7	14.6	96 <sup>2</sup> 56 <sup>3</sup> 47 <sup>4</sup>	75-132 <sup>2</sup> 38-66 <sup>3</sup> 30-53 <sup>4</sup>	Meets pool freq & LWD recruitment standards channel width # pools/mile 5 feet 184	Meets pool freq standards but not LWD	Does not meet pool freq standards

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DC Lovel II Street	om Cumicai Data	PAC FISH	Amend 29	NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics) Both (Bold & Italics)	R6 Level II Strea	ım Survey Data	RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	
			26 <sup>5</sup>	15-26 <sup>5</sup>	10 " 96 15 " 70 20 " 56 25 " 47 50 " 26	recruitment		
Pool Quality	11>1m deep pools, Max spot temp 66.2F	4 >1m deep pools, Max spot temp 66.2F	-	-	Pools >1m (3.28ft) deep, good cover, cool water, minimal filling	Few >1m pools or inadequate cover/temp, moderate filling	No >1m pools & inadequate cover/temp, major filling with sediment	
Percent Pools	-	-	-	-	-	-	-	
Bankfull (B) or Wetted (W) W/D Ratio	B 11.1	B 10.3	<10 <sup>6</sup>	<10 <sup>6</sup>	<10 <sup>7</sup>	10-12 <sup>7</sup>	>12 <sup>7</sup>	
D50 (mm), or Dominant Substrate & Embeddedness	11	11	-	Embedded <=20%	Dominant substrate gravel (2-64 mm) or cobble (64-256 mm) (interstitial spaces clear), or embeddedness <20%	Gravel or cobble subdominant, or embeddedness 20-30% if dominant	Bedrock, sand, silt, or small gravel dominant, or embeddedness >30% if gravel or cobble dominant	
Pct Fines <2 mm in Riffles (R) or Pool Tails (P)	9	9	-	-	<12% fines <sup>8</sup> in gravel	12-20% fines <sup>8</sup> in gravel	>20% fines <sup>8</sup> in gravel	
Percent Stable Banks (CS & FB)	100	100	>80	>90	>90% stable	80-90% stable	< 80% stable	
Percent Stable Banks (CS, FB, US)	-	-	-	-	-	-	-	

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	Do Laval III Owa	O	PAC	Amend 29		of Pathways and anges of Criteria	Indicators
(Italics) Both (Bold & Italics)	R6 Level II Strea	m Survey Data	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning
Percent Undercut Banks	-	-	>75	50-75% undercut <sup>9</sup>	-	-	-
Large Wood Frequency (#/mi) <sup>14</sup>	12.0 <sup>10</sup> , low recruitment	14 <sup>10,</sup> low recruitment	>20 <sup>13</sup>	20-70 <sup>10</sup> 80-120 <sup>11</sup> 100-350 <sup>12</sup>	>20 <sup>13</sup> and adequate sources for recruitment	>20 but lacks recruitment to maintain	<20 and lacks recruitment
Percent Shade/Canopy Closure	-	-	-	40-55 <sup>15</sup> 50-65 <sup>16</sup> 60-75 <sup>17</sup> 80 <sup>18</sup>	-	-	-
Greenline Wetland Rating	-	-	-	-	-	-	-
Greenline Woody Cover	-	-	-	-	-	-	-
Physical Man-made Barriers <sup>19</sup>	None	2 Barrier Culverts	-	-	Any in watershed allow passage @ all flows	Any don't allow passage @ base flows	Any don't allow passage @ range of flows
Refugia	Side channels on 1.2% of reach.	Side channels on 3.7% of reach.	-	-	Low energy backwaters & side channels	Some backwaters & high energy side channels	Few or no backwaters

Notes: 1) All PIBO data units converted from metric to English except for mm measurements; 2) Channels of <10 feet in width; 3) Channels of >10 to 20 feet in width; 4) Channels of >20 to 25 feet in width; 5) Channels of >25 to 50 feet in width; 6) Criteria is for wetted W/D ratio; 7) Criteria is for bankfull W/D ratio; 8) Fines defined as <0.85mm in gravel; 9) In non-forested systems with 2% or less gradient; 10) In Ponderosa pine ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 11) In mixed conifer ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 12) In Lodgepole pine ecosystems (at least 6 inches in diameter and 10% > 12 inches in diameter; and at least 18 feet long or 1.5 times bankfull width); 13) LWD defined as >12 inch diameter and > 35 ft length; 14) Stream surveys conducted in 1995 and earlier a) included not only LW material within the bankfull channel, but also leaning trees that have the potential to fall into the stream, and b) included a "Brush" LWD category

that is not considered functional LWD as per Amendment 29 DFCs and the MPI unless in Lodgepole Pine ecosystems. Stream surveys conducted in 1996 and later **a)** only included trees actually within the bankfull channel interacting with stream flow during bankfull conditions, and **b)** included a "Small" LWD category that is not considered functional LWD as described above; **15)** In Ponderosa pine ecosystems; **16)** In mixed conifer ecosystems; **17)** In Lodgepole pine ecosystems; **18)** In hardwood/meadow complexes; **19)** Culvert barrier data from MNF Culvert Assessment GIS layer.

Table 9. Summary of PIBO Effectiveness Monitoring Data vs. Fish Habitat Standards for Streams within Allotments.

Murderers Creek

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DIDO Effectivenes	an Manitarian Data	PAC	Amend 29		of Pathways and anges of Criteria	At Risk Not Properly Functioning	
(Italics) Both (Bold & Italics)	PIBO Effectivenes	ss Monitoring Data	FISH RMO	DFC	Properly Functioning	At Risk		
Stream Name	Murderers Cr Reach 1	Murderers Cr Reach 1	-	-	-	-	-	
Pasture Name	Tex Cr Gather	Tex Cr Gather	-	-	-	-	-	
Survey Date	2003	2008	-	-	-	-	-	
Sample Type	I	I	-	-	-	-	-	
6 <sup>th</sup> Field HUC	170702010301	6579	-	-	-	-	-	
Av Bankfull (B) and/or Wetted (W) Width (feet)	-	-	-	-	-	-	-	
Av Gradient (%)	-	-	-	-	-	-	-	
Residual Pool Depth (feet)	0.37	0.53	-	-	-	-	-	
Pool Frequency (#/mi)	-	-	96 <sup>2</sup> 56 <sup>3</sup> 47 <sup>4</sup> 26 <sup>5</sup>	75-132 <sup>2</sup> 38-66 <sup>3</sup> 30-53 <sup>4</sup> 15-26 <sup>5</sup>	Meets pool freq & LWD recruitment standards channel width # pools/mile 5 feet 184			

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DIDO Effectiveness	as Manitarian Data	PAC FISH	Amend 29		of Pathways and anges of Criteria	I Indicators
(Italics) Both (Bold & Italics)	PIBO Effectivenes	ss Monitoring Data	RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning
					10 " 96 15 " 70 20 " 56 25 " 47 50 " 26		
Pool Quality	-	-	-	-	Pools >1m (3.28ft) deep, good cover, cool water, minimal filling	Few >1m pools or inadequate cover/temp, moderate filling	No >1m pools & inadequate cover/temp, major filling with sediment
Percent Pools	78.7	43.5	-	-	-	-	-
Bankfull (B) or Wetted (W) W/D Ratio	B 14.5	B 14.1	<10 <sup>6</sup>	<10 <sup>6</sup>	<10 <sup>7</sup>	10-12 <sup>7</sup>	>12 <sup>7</sup>
D50 (mm), or Dominant Substrate & Embeddedness	0.01	0.01	-	Embedded <=20%	Dominant substrate gravel (2-64 mm) or cobble (64-256 mm) (interstitial spaces clear), or embeddedness <20%	Gravel or cobble subdominant, or embeddedness 20-30% if dominant	Bedrock, sand, silt, or small gravel dominant, or embeddedness >30% if gravel or cobble dominant
Pct Fines <2 mm in Riffles (R) or Pool Tails (P)	P 40.5	P 37.7	-	-	<12% fines <sup>8</sup> in gravel	12-20% fines <sup>8</sup> in gravel	>20% fines <sup>8</sup> in gravel
Percent Stable Banks (CS & FB)	72.7	93.2	>80	>90	>90% stable	80-90% stable	< 80% stable
Percent Stable Banks (CS, FB, US)	-	-	-	-	-	-	-

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DIDO Effective con	Maritanian Bata	PAC	Amend 29		of Pathways and anges of Criteria	
(Italics) Both (Bold & Italics)	PIBO Effectivenes	ss Monitoring Data	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning
Percent Undercut Banks	39.5	43.2	>75	50-75% undercut <sup>9</sup>	-	-	-
Large Wood Frequency (#/mi) <sup>14</sup>		-	>20 <sup>13</sup>	20-70 <sup>10</sup> 80-120 <sup>11</sup> 100-350 <sup>12</sup>	>20 <sup>13</sup> and adequate sources for recruitment	>20 but lacks recruitment to maintain	<20 and lacks recruitment
Percent Shade/Canopy Closure	-	-	-	40-55 <sup>15</sup> 50-65 <sup>16</sup> 60-75 <sup>17</sup> 80 <sup>18</sup>	-	-	-
Greenline Wetland Rating	72.4	66.5	-	-	-	-	-
Greenline Woody Cover	44.5	36.4	-	-	-	-	-
Physical Man-made Barriers <sup>19</sup>		-	-	-	Any in watershed allow passage @ all flows	Any don't allow passage @ base flows	Any don't allow passage @ range of flows
Off-channel Habitat & Refugia	-	-	-	-	Low energy backwaters & side channels	Some backwaters & high energy side channels	Few or no backwaters

Notes: 1) All PIBO data units converted from metric to English except for mm measurements; 2) Channels of <10 feet in width; 3) Channels of >10 to 20 feet in width; 4) Channels of >20 to 25 feet in width; 5) Channels of >25 to 50 feet in width; 6) Criteria is for wetted W/D ratio; 7) Criteria is for bankfull W/D ratio; 8) Fines defined as <0.85mm in gravel; 9) In non-forested systems with 2% or less gradient; 10) In Ponderosa pine ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 11) In mixed conifer ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 12) In Lodgepole pine ecosystems (at least 6 inches in diameter and 10% > 12 inches in diameter; and at least 18 feet long or 1.5 times bankfull width); 13) LWD defined as >12 inch diameter and > 35 ft length; 14) Stream surveys conducted in 1995 and earlier a) included not only LW material within the bankfull channel, but also leaning trees that have the potential to fall into the stream, and b) included a "Brush" LWD category

that is not considered functional LWD as per Amendment 29 DFCs and the MPI unless in Lodgepole Pine ecosystems. Stream surveys conducted in 1996 and later **a)** only included trees actually within the bankfull channel interacting with stream flow during bankfull conditions, and **b)** included a "Small" LWD category that is not considered functional LWD as described above; **15)** In Ponderosa pine ecosystems; **16)** In mixed conifer ecosystems; **17)** In Lodgepole pine ecosystems; **18)** In hardwood/meadow complexes; **19)** Culvert barrier data from MNF Culvert Assessment GIS layer.

Table 10. Summary of Available R6 Stream Survey Data vs. Fish Habitat Standards for Streams within Allotments.

### **South Fork Deer and North Fork Deer Creeks**

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DC I av	!! С	. C	4.	PAC	Amend 29	NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics)  Both (Bold & Italics)		vel II Stream	i Survey Da	та	FISH RMO	DFC			Not Properly Functioning	
Stream Name	SF Deer Creek Reaches 1-2	SF Deer Creek Reaches 1-2	NF Deer Creek Reaches 1-4	NF Deer Creek Reaches 1-4	-	-	-	-	-	
Pasture Name	Deer Creek	Deer Creek	Deer Creek	Deer Creek	-	-	-	-	-	
Survey Date	1993 (Aug 26)	2007 (Aug 1)	1993 (Aug 2)	2007 (Jul 30-31)	-	-	-	-	-	
Sample Type	-	-	-	-	-	-	-	-	-	
6 <sup>th</sup> Field HUC	170702010305	4677	6677	4633	-	-	-	-	-	
Av Bankfull (B) and/or Wetted (W) Width (feet)	B 6.1 W 5.7	W 2.8	B 7.9 W 6.8	W 5.6	-	-	-	-	-	
Av Gradient (%)	2.5	3.2	4.5	3.9	-	-	-	-	-	
Residual Pool Depth (feet)	1.0	0.7	1.1	1.1	-	-	-	-	-	

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DO L		0		PAC	Amend 29		of Pathways and anges of Criteria	I Indicators
(Italics) Both (Bold & Italics)	R6 Lev	el II Stream	i Survey Da	та	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning
Pool Frequency (#/mi)	72.9	4.7	73.0	13.1	96 <sup>2</sup> 56 <sup>3</sup> 47 <sup>4</sup> 26 <sup>5</sup>	75-132 <sup>2</sup> 38-66 <sup>3</sup> 30-53 <sup>4</sup> 15-26 <sup>5</sup>	Meets pool freq & LWD recruitment standards channel width # pools/mile 5 feet 184 10 " 96 15 " 70 20 " 56 25 " 47 50 " 26	Meets pool freq standards but not LWD recruitment	Does not meet pool freq standards
Pool Quality	No >1m deep pools, Max spot temp 53.0F	No >1m deep pools, Max spot temp 59.0F	8 >1m deep pools, Max spot temp 61.0F	No>1m deep pools, Max spot temp 63.0F	-	-	Pools >1m (3.28ft) deep, good cover, cool water, minimal filling	Few >1m pools or inadequate cover/temp, moderate filling	No >1m pools & inadequate cover/temp, major filling with sediment
Percent Pools	67.1	2.6	43.0	-	-	-	-	-	-
Bankfull (B) or Wetted (W) W/D Ratio	B 5.1 W 9.8	B 11.2	B 6.7	B 9.3	<10 <sup>6</sup>	<10 <sup>6</sup>	<10 <sup>7</sup>	10-12 <sup>7</sup>	>12 <sup>7</sup>
D50 (mm), or Dominant Substrate & Embeddedness	Gravel, Embeddednes s < 35%	Sand, Embedde dness >35%	Gravel, Embedde dness <35%	Sand (77.8%) Embedde dness >35%	-	Embedded <=20%	Dominant substrate gravel (2-64 mm) or cobble (64-256 mm) (interstitial spaces clear), or embeddedness <20%	Gravel or cobble subdominant, or embeddedness 20-30% if dominant	Bedrock, sand, silt, or small gravel dominant, or embeddedness >30% if gravel or cobble dominant
Pct Fines <2 mm in Riffles (R) or Pool Tails (P)	-	-	-	-	-	-	<12% fines <sup>8</sup> in gravel	12-20% fines <sup>8</sup> in gravel	>20% fines <sup>8</sup> in gravel

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DC L ov		. C D.	4.	PAC	Amend 29		of Pathways and anges of Criteria	Indicators
(Italics) Both (Bold & Italics)	Ro Lev	vel II Stream	i Survey Da	та	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning
Percent Stable Banks (CS & FB)	-	100	-	99.6	>80	>90	>90% stable	80-90% stable	< 80% stable
Percent Stable Banks (CS, FB, US)	-	-	-	-	-	-	-	-	-
Percent Undercut Banks	-	-	-	-	>75	50-75% undercut <sup>9</sup>	-	-	-
Large Wood Frequency (#/mi) <sup>14</sup>	30.5 <sup>10</sup> , Poor Recruitment	9 <sup>10</sup> , Poor Recruitme nt	62 <sup>10</sup>	9 <sup>10</sup>	>20 <sup>13</sup>	20-70 <sup>10</sup> 80-120 <sup>11</sup> 100-350 <sup>12</sup>	>20 <sup>13</sup> and adequate sources for recruitment	>20 but lacks recruitment to maintain	<20 and lacks recruitment
Percent Shade/Canopy Closure	-	49%	-	45.0	-	40-55 <sup>15</sup> 50-65 <sup>16</sup> 60-75 <sup>17</sup> 80 <sup>18</sup>	-	-	-
Greenline Wetland Rating	-	-	-	-	-	-	-	-	-
Greenline Woody Cover	-	-	-	-	-	-	-	-	-
Physical Man-made Barriers <sup>19</sup>	2 culvert barriers	2 culvert barriers	2 culvert barriers	2 culvert barriers	-	-	Any in watershed allow passage @ all flows	Any don't allow passage @ base flows	Any don't allow passage @ range of flows
Off-channel Habitat & Refugia	Side channels on 0.2% of reaches	Side channels on 7.7% of reaches	Side channels on 3.6% of reaches	Side channels on 0.6% of reaches	-	-	Low energy backwaters & side channels	Some backwaters & high energy side channels	Few or no backwaters

Notes: 1) All PIBO data units converted from metric to English except for mm measurements; 2) Channels of <10 feet in width; 3) Channels of >10 to 20 feet in width; 4) Channels of >20 to 25 feet in width; 5) Channels of >25 to 50 feet in width; 6) Criteria is for wetted W/D ratio; 7)

Criteria is for bankfull W/D ratio; **8)** Fines defined as <0.85mm in gravel; **9)** In non-forested systems with 2% or less gradient; **10)** In Ponderosa pine ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); **11)** In mixed conifer ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); **12)** In Lodgepole pine ecosystems (at least 6 inches in diameter and 10% > 12 inches in diameter; and at least 18 feet long or 1.5 times bankfull width); **13)** LWD defined as >12 inch diameter and > 35 ft length; **14)** Stream surveys conducted in 1995 and earlier **a)** included not only LW material within the bankfull channel, but also leaning trees that have the potential to fall into the stream, and **b)** included a "Brush" LWD category that is not considered functional LWD as per Amendment 29 DFCs and the MPI unless in Lodgepole Pine ecosystems. Stream surveys conducted in 1996 and later **a)** only included trees actually within the bankfull channel interacting with stream flow during bankfull conditions, and **b)** included a "Small" LWD category that is not considered functional LWD as described above; **15)** In Ponderosa pine ecosystems; **16)** In mixed conifer ecosystems; **17)** In Lodgepole pine ecosystems; **18)** In hardwood/meadow complexes; **19)** Culvert barrier data from MNF Culvert Assessment GIS layer.

Table 11. Summary of PIBO Effectiveness Monitoring Data vs. Fish Habitat Standards for Streams within Allotments.

#### **South Fork Murderers and Deer Creeks**

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	PIBO Effectiveness Monitoring Data			PAC FISH			NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics) Both (Bold & Italics)		tiveness Monito	ring Data	RMO	DFC	Properly Functioning	Not Properly Functioning			
Stream Name	SF Murderers Cr Reach 1	SF Murderers Cr Reach 1	Deer Creek Reach 5	1	-	-	-	-		
Pasture Name	Timber Mountain	Timber Mountain	Deer Creek	ı	1	-	-	-		
Survey Date	2003	2008	2008		-	-	-	-		
Sample Type	I	I	К	-	-	-	-	-		
6 <sup>th</sup> Field HUC	170702010402	66.77	170702010205	-	-	-	-	-		
Av Bankfull (B) and/or Wetted (W) Width (feet)	-	-	-	-	-	-	-	-		
Av Gradient (%)	-	-	-	-	-	-	-	-		

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DIDO E#ss	4i	nin n Data	PAC	Amend 29		of Pathways and anges of Criteria	Indicators
(Italics) Both (Bold & Italics)	PIBO Effec	tiveness Monito	ring Data	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning
Residual Pool Depth (feet)	0.19	0.16	0.39	-	-	-	-	-
Pool Frequency (#/mi)	-	-	-	96 <sup>2</sup> 56 <sup>3</sup> 47 <sup>4</sup> 26 <sup>5</sup>	75-132 <sup>2</sup> 38-66 <sup>3</sup> 30-53 <sup>4</sup> 15-26 <sup>5</sup>	Meets pool freq & LWD recruitment standards channel width # pools/mile 5 feet 184 10 " 96 15 " 70 20 " 56 25 " 47 50 " 26	Meets pool freq standards but not LWD recruitment	Does not meet pool freq standards
Pool Quality	-	-	-	-	-	Pools >1m (3.28ft) deep, good cover, cool water, minimal filling	Few >1m pools or inadequate cover/temp, moderate filling	No >1m pools & inadequate cover/temp, major filling with sediment
Percent Pools	11.4	13.1	62.1	-	-	-	-	-
Bankfull (B) or Wetted (W) W/D Ratio	B 71.2	B 40.3	B 17.6	<10 <sup>6</sup>	<10 <sup>6</sup>	<10 <sup>7</sup>	10-12 <sup>7</sup>	>12 <sup>7</sup>
D50 (mm), or Dominant Substrate & Embeddedness	0.02	0.04	-	-	Embedded <=20%	Dominant substrate gravel (2-64 mm) or cobble (64-256 mm) (interstitial spaces clear), or embeddedness <20%	Gravel or cobble subdominant, or embeddedness 20-30% if dominant	Bedrock, sand, silt, or small gravel dominant, or embeddedness >30% if gravel or cobble dominant
Pct Fines <2 mm in Riffles (R) or Pool Tails (P)	P 20.2	P 16.2	-	-	-	<12% fines <sup>8</sup> in gravel	12-20% fines <sup>8</sup> in gravel	>20% fines <sup>8</sup> in gravel

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DIDO E#ss	45	nin n Data	PAC	Amend 29		of Pathways and anges of Criteria	Indicators
(Italics) Both (Bold & Italics)	PIBO Effec	tiveness Monito	ring Data	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning
Percent Stable Banks (CS & FB)	45.0	95.2	88.0	>80	>90	>90% stable	80-90% stable	< 80% stable
Percent Stable Banks (CS, FB, US)	-	-	-	-	-	-	-	-
Percent Undercut Banks	2.9	2.4	21.4	>75	50-75% undercut <sup>9</sup>	-	-	-
Large Wood Frequency (#/mi) <sup>14</sup>	-	-	-	>20 <sup>13</sup>	20-70 <sup>10</sup> 80-120 <sup>11</sup> 100-350 <sup>12</sup>	>20 <sup>13</sup> and adequate sources for recruitment	>20 but lacks recruitment to maintain	<20 and lacks recruitment
Percent Shade/Canopy Closure	-	-	-	-	40-55 <sup>15</sup> 50-65 <sup>16</sup> 60-75 <sup>17</sup> 80 <sup>18</sup>	-	-	-
Greenline Wetland Rating	24.3	30.7	58.9	-	-	-	-	-
Greenline Woody Cover	22.6	17.4	17.8	-	-	-	-	-
Physical Man-made Barriers <sup>19</sup>	-	-	-	-	-	Any in watershed allow passage @ all flows	Any don't allow passage @ base flows	Any don't allow passage @ range of flows
Off-channel Habitat & Refugia	-	-	-	-	-	Low energy backwaters & side channels	Some backwaters & high energy side channels	Few or no backwaters

Notes: 1) All PIBO data units converted from metric to English except for mm measurements; 2) Channels of <10 feet in width; 3) Channels of >10 to 20 feet in width; 4) Channels of >20 to 25 feet in width; 5) Channels of >25 to 50 feet in width; 6) Criteria is for wetted W/D ratio; 7) Criteria is for bankfull W/D ratio; 8) Fines defined as <0.85mm in gravel; 9) In non-forested systems with 2% or less gradient; 10) In Ponderosa

pine ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 11) In mixed conifer ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 12) In Lodgepole pine ecosystems (at least 6 inches in diameter and 10% > 12 inches in diameter; and at least 18 feet long or 1.5 times bankfull width); 13) LWD defined as >12 inch diameter and > 35 ft length; 14) Stream surveys conducted in 1995 and earlier a) included not only LW material within the bankfull channel, but also leaning trees that have the potential to fall into the stream, and b) included a "Brush" LWD category that is not considered functional LWD as per Amendment 29 DFCs and the MPI unless in Lodgepole Pine ecosystems. Stream surveys conducted in 1996 and later a) only included trees actually within the bankfull channel interacting with stream flow during bankfull conditions, and b) included a "Small" LWD category that is not considered functional LWD as described above; 15) In Ponderosa pine ecosystems; 16) In mixed conifer ecosystems; 17) In Lodgepole pine ecosystems; 18) In hardwood/meadow complexes; 19) Culvert barrier data from MNF Culvert Assessment GIS layer.

Table 12. Summary of Available R6 Stream Survey Data vs. Fish Habitat Standards for Streams within Allotments.

South Fork Murderers Creek

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DC Lavel II Stream Survey Date				PAC FISH	Amend 29	NMFS Matrix of Pathways and Indicators Ranges of Criteria		
(Italics) Both (Bold & Italics)	R6 Level II Stream Survey Data					DFC	Properly Functioning	At Risk	Not Properly Functioning
Stream Name	SF Murderers Creek Reach 1	SF Murderers Creek Reaches 1-2	SF Murderers Creek Reaches 2-3	SF Murderers Creek Reaches 3-4	-	-	-	-	-
Pasture Name	Timber Mountain (exclosure constructed 2010)	Timber Mountain (exclosure constructe d 2010)	Blue Ridge, SF M.C. Gather	Blue Ridge	-	·	-	•	•
Survey Date	1992 (June 23-July 2)	2009 (July 8-10)	1992 (June 23-July 2)	2009 (July 8-10)	ı	-	-	-	-
Sample Type	-	-	-	-	-	-	-	-	-
6 <sup>th</sup> Field HUC	1707020104 02	6677	6679	,	-	-	-	-	-

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol (Italics) Both (Bold & Italics)	R6 Level II Stream Survey Data				PAC FISH RMO	Amend 29 DFC	NMFS Matrix of Pathways and Indicators Ranges of Criteria		
							Properly Functioning	At Risk	Not Properly Functioning
Av Bankfull (B) and/or Wetted (W) Width (feet)	W 7.9	W 12.1 B 22.7	W 7.1	W 8.8 B 13.9	-	1	-	-	-
Av Gradient (%)	2.0	3.5	3.5	5.5	-	-	-	-	-
Residual Pool Depth (feet)	0.7	1.1	1.0	1.1	-	-	-	-	-
Pool Frequency (#/mi)	32.4	36.3	59.1	81.6	96 <sup>2</sup> 56 <sup>3</sup> 47 <sup>4</sup> 26 <sup>5</sup>	75-132 <sup>2</sup> 38-66 <sup>3</sup> 30-53 <sup>4</sup> 15-26 <sup>5</sup>	Meets pool freq & LWD recruitment standards channel width # pools/mile 5 feet 184 10 " 96 15 " 70 20 " 56 25 " 47 50 " 26	Meets pool freq standards but not LWD recruitment	Does not meet pool freq standards
Pool Quality	No >1m deep pools, Max spot temp 52.0F	No >1m deep pools, Max spot temp 60.8 F	No >1m deep pools, Max spot temp 57.0F	No >1m deep pools, Max spot temp 53.6F	-	-	Pools >1m (3.28ft) deep, good cover, cool water, minimal filling	Few >1m pools or inadequate cover/temp, moderate filling	No >1m pools & inadequate cover/temp, major filling with sediment
Percent Pools	25.7	33.56	46.9	60.7	-	-	-	-	-
Bankfull (B) or Wetted (W) W/D Ratio	B 5.0	B 15.6	B 8.8	B 10.3	<10 <sup>6</sup>	<10 <sup>6</sup>	<10 <sup>7</sup>	10-12 <sup>7</sup>	>12 <sup>7</sup>
D50 (mm), or Dominant Substrate & Embeddedness	Cobble, Embeddedn ess >35%	Gravel	Cobble, Embedded ness >35%	Cobble	-	Embedded <=20%	Dominant substrate gravel (2-64 mm) or cobble (64-256 mm) (interstitial spaces	Gravel or cobble subdominant, or embeddedness 20-30% if	Bedrock, sand, silt, or small gravel dominant, or embeddedness

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	De	l III Ct	C D-	-4-	PAC FISH	Amend 29		of Pathways and anges of Criteria	I Indicators
(Italics) Both (Bold & Italics)	Ko I	Level II Strea	am Survey Da	ata	RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning
							clear), or embeddedness <20%	dominant	>30% if gravel or cobble dominant
Pct Fines <2 mm in Riffles (R) or Pool Tails (P)	-	-	-	-	-	-	<12% fines <sup>8</sup> in gravel	12-20% fines <sup>8</sup> in gravel	>20% fines <sup>8</sup> in gravel
Percent Stable Banks (CS & FB)	91.0	94.0	92.8	99.0	>80	>90	>90% stable	80-90% stable	< 80% stable
Percent Stable Banks (CS, FB, US)	-	-	-	-	-	-	-	-	-
Percent Undercut Banks	-	-	-	-	>75	50-75% undercut <sup>9</sup>	-	-	-
Large Wood Frequency (#/mi) <sup>14</sup>	7.2 <sup>10</sup> , Good recruitment	0.0	51.3 <sup>10</sup> , Good recruitment	5.0	>20 <sup>13</sup>	20-70 <sup>10</sup> 80-120 <sup>11</sup> 100-350 <sup>12</sup>	>20 <sup>13</sup> and adequate sources for recruitment	>20 but lacks recruitment to maintain	<20 and lacks recruitment
Percent Shade/Canopy Closure	63.2	-	68.05	-	-	40-55 <sup>15</sup> 50-65 <sup>16</sup> 60-75 <sup>17</sup> 80 <sup>18</sup>	-	-	-
Greenline Wetland Rating	-	-	-	-	-	-	-	-	-
Greenline Woody Cover	-	-	-	-	-	-	-	-	-
Physical Man-made Barriers <sup>19</sup>	None	None	None	None	-	-	Any in watershed allow passage @ all flows	Any don't allow passage @ base flows	Any don't allow passage @ range of flows

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	D.C.	R6 Level II Stream Survey Data				I I I I	NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics) Both (Bold & Italics)	K6	Level II Strea	im Survey Da	ata	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	
Off-channel Habitat & Refugia	Side channels on 9.6% of reach	Side channels on 5.0% of reaches	Side channels on 1.5% of reaches	Side channels on 1.8% of reaches	ı	1	Low energy backwaters & side channels	Some backwaters & high energy side channels	Few or no backwaters	
PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	<b>D</b> 0	I III 04	O		PAC	H Amend 29		of Pathways and anges of Criteria	Indicators	
(Italics) Both (Bold & Italics)	R6	Level II Strea	ım Survey Da	ata	FISH RMO		Properly Functioning	At Risk	Not Properly Functioning	
Stream Name	SF Murderers Creek Reach 4	SF Murderers Creek Reach 5	SF Murderers Creek Reaches 5	SF Murderers Creek Reach 6-7	-	-	-	-	-	
Pasture Name	Horse Mountain	South Fork M.C. Gather	Horse Mountain	Horse Mountain,	-	-	-	-	-	
Survey Date	1992 (Jun 23-Jul 2)	2009 (Jul 8- 10)	1992 (Jun 23-Jul 2)	2009 (Jul 8-10)	-	-	-	-	-	
Sample Type	-	-	-	-	-	-	-	-	-	
6 <sup>th</sup> Field HUC	707020104 025	170702010 402	170702010 402	170702010 402	-	-	-	-	-	
Av Bankfull (B) and/or Wetted (W) Width (feet)	W 4.3	W 8.6 B 11.8	W 4.9	W 8.9 B 13.3	-	-	-	-	-	
Av Gradient (%)	2	2	1.5	1	-	-	-	-	-	
Residual Pool	1.7	1.8	1.6	1.7	-	-	-	-	-	

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	P.0		0	-1-	PAC FISH	Amend 29	NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics) Both (Bold & Italics)	K6	Level II Strea	im Survey Da	ата	RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	
Depth (feet)										
Pool Frequency (#/mi)	46.4	39.0	46.8	8.3	96 <sup>2</sup> 56 <sup>3</sup> 47 <sup>4</sup> 26 <sup>5</sup>	75-132 <sup>2</sup> 38-66 <sup>3</sup> 30-53 <sup>4</sup> 15-26 <sup>5</sup>	Meets pool freq & LWD recruitment standards channel width # pools/mile 5 feet 184 10 " 96 15 " 70 20 " 56 25 " 47 50 " 26	Meets pool freq standards but not LWD recruitment	Does not meet pool freq standards	
Pool Quality	No >1m deep pools, max spot temp 70.0F	10 >1m deep pools, max spot temp 53.6F	No >1m deep pools, max spot temp 55F	2 >1m deep pools, 53.6F	-	-	Pools >1m (3.28ft) deep, good cover, cool water, minimal filling	Few >1m pools or inadequate cover/temp, moderate filling	No >1m pools & inadequate cover/temp, major filling with sediment	
Percent Pools	84.0	34.1	46.9	18	-	-	-	-	-	
Bankfull (B) or Wetted (W) W/D Ratio	B 11.0	B 10.5	B 20.3	B 11.2	<10 <sup>6</sup>	<10 <sup>6</sup>	<10 <sup>7</sup>	10-12 <sup>7</sup>	>12 <sup>7</sup>	
D50 (mm), or Dominant Substrate & Embeddedness	Sand, Embedded ness >35%	Gravel	Sand, Embedded ness not >35%	Sand	-	Embedded <=20%	Dominant substrate gravel (2-64 mm) or cobble (64-256 mm) (interstitial spaces clear), or embeddedness <20%	Gravel or cobble subdominant, or embeddedness 20-30% if dominant	Bedrock, sand, silt, or small gravel dominant, or embeddedness >30% if gravel or cobble dominant	
Pct Fines <2 mm in Riffles (R) or Pool Tails (P)	-	-	-	-	-	-	<12% fines <sup>8</sup> in gravel	12-20% fines <sup>8</sup> in gravel	>20% fines <sup>8</sup> in gravel	

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	D.C.	R6 Level II Stream Survey Data						of Pathways and anges of Criteria	Indicators
(Italics) Both (Bold & Italics)	Ro	Level II Strea	am Survey Da	ata	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning
Percent Stable Banks (CS & FB)	88.0	92.0	86.8	94.0	>80	>90	>90% stable	80-90% stable	< 80% stable
Percent Stable Banks (CS, FB, US)	-	-	-	-	-	-	-	-	-
Percent Undercut Banks	-	-	-	-	>75	50-75% undercut <sup>9</sup>	-	-	-
Large Wood Frequency (#/mi) <sup>14</sup>	30.4 <sup>10</sup> , Good Recruitmen t	5.0 <sup>10</sup>	8.5 <sup>10</sup> , Poor Recruitmen t	8.0 <sup>10</sup>	>20 <sup>13</sup>	20-70 <sup>10</sup> 80-120 <sup>11</sup> 100-350 <sup>12</sup>	>20 <sup>13</sup> and adequate sources for recruitment	>20 but lacks recruitment to maintain	<20 and lacks recruitment
Percent Shade/Canopy Closure	41.0	-	23.9	-	-	40-55 <sup>15</sup> 50-65 <sup>16</sup> 60-75 <sup>17</sup> 80 <sup>18</sup>	-	-	-
Greenline Wetland Rating	-	-	-	-	-	-	-	-	-
Greenline Woody Cover	-	-	-	-	-	-	-	-	-
Physical Man-made Barriers <sup>19</sup>	None	None	None	1 Culvert barrier	-	-	Any in watershed allow passage @ all flows	Any don't allow passage @ base flows	Any don't allow passage @ range of flows
Off-channel Habitat & Refugia	Side channels on 1.5% of reach	No side channels on reach	Side channels on 5.8% of reach	No side channels on reaches	-	-	Low energy backwaters & side channels	Some backwaters & high energy side channels	Few or no backwaters
PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	R6 Level II Stream Survey Data			ata	PAC FISH	Amend 29 DFC	NMFS Matrix of Pathways and Indicators Ranges of Criteria		

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	D.C.	Laval II Ctua	C		FISH	Amend 29		of Pathways and anges of Criteria	Indicators
(Italics) Both (Bold & Italics)		Level II Strea	am Survey Da	ata	RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning
(Italics) Both (Bold & Italics)					RMO		Properly Functioning	At Risk	Not Properly Functioning
Stream Name	SF Murderers Creek Reach 7	SF Murderers Creek Reach 8	SF Murderers Creek Reaches 8	SF Murderers Creek Reach 9	-	-	-	-	-
Pasture Name	John Young Cow Camp	John Young Cow Camp	John Young Meadow	John Young Meadow	-	-	-	-	-
Survey Date	1992 (Jun 23-Jul 2)	2009( Jul 8- 10)	1992 (Jun 23-Jul 2)	2009 (Jul 8-10)	-	-	-	-	-
Sample Type	-	-	-	-	-	-	-	-	-
6 <sup>th</sup> Field HUC	170702010 402	6679	6623	423	-	-	-	-	-
Av Bankfull (B) and/or Wetted (W) Width (feet)	W 2.7	W 12.4 B 6	W 6.0	W 3.8 B 7.5	-	-	-	-	-
Av Gradient (%)	1	1	2	1	-	-	-	-	-
Residual Pool Depth (feet)	0.6	1.5	1.4	1.5	-	-	-	-	-
Pool Frequency (#/mi)	95.6	1.7	25.4	1.2	96 <sup>2</sup> 56 <sup>3</sup> 47 <sup>4</sup> 26 <sup>5</sup>	75-132 <sup>2</sup> 38-66 <sup>3</sup> 30-53 <sup>4</sup> 15-26 <sup>5</sup>	Meets pool freq & LWD recruitment standards channel width # pools/mile 5 feet 184 10 " 96 15 " 70	Meets pool freq standards but not LWD recruitment	Does not meet pool freq standards

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	Survey Protocol		···· C······ D	-1-	PAC FISH	Amend 29		of Pathways and anges of Criteria	Indicators
(Italics) Both (Bold & Italics)	Ro	Level II Strea	im Survey Da	ata	RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning
							20 " 56 25 " 47 50 " 26		
Pool Quality	No >1m deep pools, max spot temp 61.0F	No >1m deep pools, max spot temp 57.2F	No >1m deep pools, max spot temp 57.0F	No >1m deep pools, max spot temp 64.4F	-	-	Pools >1m (3.28ft) deep, good cover, cool water, minimal filling	Few >1m pools or inadequate cover/temp, moderate filling	No >1m pools & inadequate cover/temp, major filling with sediment
Percent Pools	63.1	0.4	97.0	0.6	-	-	-	-	-
Bankfull (B) or Wetted (W) W/D Ratio	B 3.9	B 7.5	-	B 6.3	<10 <sup>6</sup>	<10 <sup>6</sup>	<10 <sup>7</sup>	10-12 <sup>7</sup>	>12 <sup>7</sup>
D50 (mm), or Dominant Substrate & Embeddedness	Sand, Embedded ness >35%	Sand	Sand, Embedded ness >35%	Sand	-	Embedded <=20%	Dominant substrate gravel (2-64 mm) or cobble (64-256 mm) (interstitial spaces clear), or embeddedness <20%	Gravel or cobble subdominant, or embeddedness 20-30% if dominant	Bedrock, sand, silt, or small gravel dominant, or embeddedness >30% if gravel or cobble dominant
Pct Fines <2 mm in Riffles (R) or Pool Tails (P)	-	-	-	-	-	-	<12% fines <sup>8</sup> in gravel	12-20% fines <sup>8</sup> in gravel	>20% fines <sup>8</sup> in gravel
Percent Stable Banks (CS & FB)	96.8	100	99.8	93.6	>80	>90	>90% stable	80-90% stable	< 80% stable
Percent Stable Banks (CS, FB, US)	-	-	-	-	-	-	-	-	-
Percent Undercut	-	-	-	-	>75	50-75%	-	-	-

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	D.C.	Laval II Ctras	C	-1-	PAC FISH	H   Amena 29	NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics) Both (Bold & Italics)	Ko	Level II Strea	am Survey Da	ata	RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	
Banks						undercut <sup>9</sup>				
Large Wood Frequency (#/mi) <sup>14</sup>	0.0 <sup>10</sup> , Poor Recruitmen t	2.010	4.5 <sup>10</sup> , Poor Recruitmen t	0.010	>20 <sup>13</sup>	20-70 <sup>10</sup> 80-120 <sup>11</sup> 100-350 <sup>12</sup>	>20 <sup>13</sup> and adequate sources for recruitment	>20 but lacks recruitment to maintain	<20 and lacks recruitment	
Percent Shade/Canopy Closure	32.7	-	22.7	-	-	40-55 <sup>15</sup> 50-65 <sup>16</sup> 60-75 <sup>17</sup> 80 <sup>18</sup>	-	-	-	
Greenline Wetland Rating	-	-	-	-	-	-	-	-	-	
Greenline Woody Cover	-	-	-	-	-	-	-	-	-	
Physical Man-made Barriers <sup>19</sup>	None	None	1 culvert barrier	1 culvert barrier	-	-	Any in watershed allow passage @ all flows	Any don't allow passage @ base flows	Any don't allow passage @ range of flows	
Off-channel Habitat & Refugia	Side channels on 25.5% of reach (beaver complex)	No side channel habitat	Side channels on 2.1% of reach	No side channel habitat	-	-	Low energy backwaters & side channels	Some backwaters & high energy side channels	Few or no backwaters	

Notes: 1) All PIBO data units converted from metric to English except for mm measurements; 2) Channels of <10 feet in width; 3) Channels of >10 to 20 feet in width; 4) Channels of >20 to 25 feet in width; 5) Channels of >25 to 50 feet in width; 6) Criteria is for wetted W/D ratio; 7) Criteria is for bankfull W/D ratio; 8) Fines defined as <0.85mm in gravel; 9) In non-forested systems with 2% or less gradient; 10) In Ponderosa pine ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 11) In mixed conifer ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 12) In Lodgepole pine ecosystems (at least 6 inches in diameter and 10% > 12 inches in diameter; and at least 18 feet long or 1.5 times bankfull width); 13) LWD defined as >12 inch diameter and > 35 ft length; 14) Stream surveys conducted in 1995 and earlier a) included not only LW

material within the bankfull channel, but also leaning trees that have the potential to fall into the stream, and **b**) included a "Brush" LWD category that is not considered functional LWD as per Amendment 29 DFCs and the MPI unless in Lodgepole Pine ecosystems. Stream surveys conducted in 1996 and later **a**) only included trees actually within the bankfull channel interacting with stream flow during bankfull conditions, and **b**) included a "Small" LWD category that is not considered functional LWD as described above; **15**) In Ponderosa pine ecosystems; **16**) In mixed conifer ecosystems; **17**) In Lodgepole pine ecosystems; **18**) In hardwood/meadow complexes; **19**) Culvert barrier data from MNF Culvert Assessment GIS layer.

Table 13. Summary of Available R6 Stream Survey Data vs. Fish Habitat Standards for Streams within Allotments.

Tex, Dans, and Orange Creeks

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DC L ev	val II Straam Surra	ov Dete	PAC FISH	H Amena 29	NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics) Both (Bold & Italics)		el II Stream Surv	ey Data	RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	
Stream Name	Tex Creek Reach 1	Dans Creek Reach 1	Orange Creek Reach 1	-	-	-	-	-	
Pasture Name	Tex Creek Gather	Dans Creek	Dans Creek	-	-	-	-	-	
Survey Date	1995 (Aug 16- 29)	1992 (June 25)	1992 (June 26)	-	-	-	-	-	
Sample Type	-	-	-	-	-	-	-	-	
6 <sup>th</sup> Field HUC	170702010301	170702010401	170702010401	-	-	-	-	-	
Av Bankfull (B) and/or Wetted (W) Width (feet)	B 15.4 W 7.8	W 4.5	W 2.5	-	-	-	-	-	
Av Gradient (%)	2.0	4.0	7.0	-	-	-	-	-	
Residual Pool Depth (feet)	1.1	0.7	0.5	-	-	-	-	-	
Pool Frequency	35.5	63.5	38.2	96 <sup>2</sup> 56 <sup>3</sup>	75-132 <sup>2</sup> 38-66 <sup>3</sup>	Meets pool freq & LWD recruitment standards	Meets pool freq standards but	Does not meet pool freq standards	

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DC L ···		Data	PAC	Amend 29	NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics) Both (Bold & Italics)	Ko Lev	vel II Stream Surv	ey Data	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	
(#/mi)				47 <sup>4</sup> 26 <sup>5</sup>	30-53 <sup>4</sup> 15-26 <sup>5</sup>	channel width # pools/mile 5 feet 184 10 " 96 15 " 70 20 " 56 25 " 47 50 " 26	not LWD recruitment		
Pool Quality	Max spot temp 60.0F	No >1m deep pools, max spot temp 50.0F	No >1m deep pools, Max spot temp 52.0F	-	-	Pools >1m (3.28ft) deep, good cover, cool water, minimal filling	Few >1m pools or inadequate cover/temp, moderate filling	No >1m pools & inadequate cover/temp, major filling with sediment	
Percent Pools	60.4	43.0	89.2	-	-	-	-	-	
Bankfull (B) or Wetted (W) W/D Ratio	B 26.5	B 8.1	B 8.2	<10 <sup>6</sup>	<10 <sup>6</sup>	<10 <sup>7</sup>	10-12 <sup>7</sup>	>12 <sup>7</sup>	
D50 (mm), or Dominant Substrate & Embeddedness	Gravel, Embeddednes s >20%	Sand, Embeddedness >35%	Sand, Embeddedness >35%	-	Embedded <=20%	Dominant substrate gravel (2-64 mm) or cobble (64-256 mm) (interstitial spaces clear), or embeddedness <20%	Gravel or cobble subdominant, or embeddedness 20-30% if dominant	Bedrock, sand, silt, or small gravel dominant, or embeddedness >30% if gravel or cobble dominant	
Pct Fines <2 mm in Riffles (R) or Pool Tails (P)	-	-	-	-		<12% fines <sup>8</sup> in gravel	12-20% fines <sup>8</sup> in gravel	>20% fines <sup>8</sup> in gravel	
Percent Stable	80-90	-	77.0	>80	>90	>90% stable	80-90% stable	< 80% stable	

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DC L o	val II Straam Surra	ou Data	PAC FISH	Amend 29	NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics) Both (Bold & Italics)	Ko Lev	el II Stream Surv	ey Data	RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	
Banks (CS & FB)									
Percent Stable Banks (CS, FB, US)	-	-	-	-	-	-	-	-	
Percent Undercut Banks	-	-	-	>75	50-75% undercut <sup>9</sup>	-	-	-	
Large Wood Frequency (#/mi) <sup>14</sup>	4.0 <sup>10</sup>	89.2 <sup>10</sup> , Poor Recruitment	37.6 <sup>11</sup> , Poor Recruitment	>20 <sup>13</sup>	20-70 <sup>10</sup> 80-120 <sup>11</sup> 100-350 <sup>12</sup>	>20 <sup>13</sup> and adequate sources for recruitment	>20 but lacks recruitment to maintain	<20 and lacks recruitment	
Percent Shade/Canopy Closure	23.0	61.5	77.0	-	40-55 <sup>15</sup> 50-65 <sup>16</sup> 60-75 <sup>17</sup> 80 <sup>18</sup>	-	-	-	
Greenline Wetland Rating	-	-	-	-	-	-	-	-	
Greenline Woody Cover	-	-	-	-	-	-	-	-	
Physical Man-made Barriers <sup>19</sup>	One Barrier Culvert	2 barrier culverts	None	-	-	Any in watershed allow passage @ all flows	Any don't allow passage @ base flows	Any don't allow passage @ range of flows	
Off-channel Habitat & Refugia	-	Side channels on 0.3% of reaches	Side channels on 0.2% of reaches	-	-	Low energy backwaters & side channels	Some backwaters & high energy side channels	Few or no backwaters	

Notes: 1) All PIBO data units converted from metric to English except for mm measurements; 2) Channels of <10 feet in width; 3) Channels of >10 to 20 feet in width; 4) Channels of >20 to 25 feet in width; 5) Channels of >25 to 50 feet in width; 6) Criteria is for wetted W/D ratio; 7) Criteria is for bankfull W/D ratio; 8) Fines defined as <0.85mm in gravel; 9) In non-forested systems with 2% or less gradient; 10) In Ponderosa

pine ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 11) In mixed conifer ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 12) In Lodgepole pine ecosystems (at least 6 inches in diameter and 10% > 12 inches in diameter; and at least 18 feet long or 1.5 times bankfull width); 13) LWD defined as >12 inch diameter and > 35 ft length; 14) Stream surveys conducted in 1995 and earlier a) included not only LW material within the bankfull channel, but also leaning trees that have the potential to fall into the stream, and b) included a "Brush" LWD category that is not considered functional LWD as per Amendment 29 DFCs and the MPI unless in Lodgepole Pine ecosystems. Stream surveys conducted in 1996 and later a) only included trees actually within the bankfull channel interacting with stream flow during bankfull conditions, and b) included a "Small" LWD category that is not considered functional LWD as described above; 15) In Ponderosa pine ecosystems; 16) In mixed conifer ecosystems; 17) In Lodgepole pine ecosystems; 18) In hardwood/meadow complexes; 19) Culvert barrier data from MNF Culvert Assessment GIS layer.

Table 14. Summary of PIBO Effectiveness Monitoring Data vs. Fish Habitat Standards for Streams within Allotments.

Thorn Creek

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DIDO E#	PIBO Effectiveness Monitoring Data					NMFS Matrix of Pathways and Indicators Ranges of Criteria			
(Italics) Both (Bold & Italics)		ectiveness	wonitoring i	Data	FISH RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning	
Stream Name	Thorn Cr Reach 1	Thorn Cr Reach 1	Thorn Cr Reach 1	Thorn Cr Reach 1	-	-	-	-	-	
Pasture Name	Martin Corrals	Martin Corrals	Martin Corrals	Martin Corrals	-	-	-	-	-	
Survey Date	2003	2008	2003	2008	-	-	-	-	-	
Sample Type	I	I	К	К	-	-	-	-	-	
6 <sup>th</sup> Field HUC	170702010403	6679	6679	4477	-	-	-	-	-	
Av Bankfull (B) and/or Wetted (W) Width (feet)	-	-	-	-	-	-	-	-	-	
Av Gradient (%)	-	-	-	-	-	-	-	-	-	
Residual Pool	0.19	0.16	-	0.19	-	-	-	-	-	

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DIDO E#	i	Manitanina I	Dete	PAC FISH	Amend 29		of Pathways and anges of Criteria	Indicators
(Italics) Both (Bold & Italics)	PIBO ETTO	ectiveness	Monitoring	Data	RMO	DFC	Properly Functioning	At Risk	Not Properly Functioning
Depth (feet)									
Pool Frequency (#/mi)	-	-	-	-	96 <sup>2</sup> 56 <sup>3</sup> 47 <sup>4</sup> 26 <sup>5</sup>	75-132 <sup>2</sup> 38-66 <sup>3</sup> 30-53 <sup>4</sup> 15-26 <sup>5</sup>	Meets pool freq & LWD recruitment standards channel width # pools/mile 5 feet 184 10 " 96 15 " 70 20 " 56 25 " 47 50 " 26	Meets pool freq standards but not LWD recruitment	Does not meet pool freq standards
Pool Quality	-	-	-	-	-	-	Pools >1m (3.28ft) deep, good cover, cool water, minimal filling	Few >1m pools or inadequate cover/temp, moderate filling	No >1m pools & inadequate cover/temp, major filling with sediment
Percent Pools	66.5	28.0	-	29.1	-	-	-	-	-
Bankfull (B) or Wetted (W) W/D Ratio	B 19.7	B 20.6	-	B 20.8	<10 <sup>6</sup>	<10 <sup>6</sup>	<10 <sup>7</sup>	10-12 <sup>7</sup>	>12 <sup>7</sup>
D50 (mm), or Dominant Substrate & Embeddedness	0.01	0.01	-	-	-	Embedded <=20%	Dominant substrate gravel (2-64 mm) or cobble (64-256 mm) (interstitial spaces clear), or embeddedness <20%	Gravel or cobble subdominant, or embeddedness 20-30% if dominant	Bedrock, sand, silt, or small gravel dominant, or embeddedness >30% if gravel or cobble dominant
Pct Fines <2 mm in Riffles (R) or Pool Tails (P)	P 49.7	P 71.4	-	-	-	-	<12% fines <sup>8</sup> in gravel	12-20% fines <sup>8</sup> in gravel	>20% fines <sup>8</sup> in gravel

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol (Italics) Both (Bold & Italics)	DIDO Effections on Marifestian Date			PAC FISH RMO	Amend 29 DFC	NMFS Matrix of Pathways and Indicators Ranges of Criteria			
	PIBO Effectiveness Monitoring Data					Properly Functioning	At Risk	Not Properly Functioning	
Percent Stable Banks (CS & FB)	59.1	58.7	59.5	92.9	>80	>90	>90% stable	80-90% stable	< 80% stable
Percent Stable Banks (CS, FB, US)	-	-	-	-	-	-	-	-	-
Percent Undercut Banks	13.6	17.4	7.3	4.9	>75	50-75% undercut <sup>9</sup>	-	-	-
Large Wood Frequency (#/mi) <sup>14</sup>	-	-	-	-	>20 <sup>13</sup>	20-70 <sup>10</sup> 80-120 <sup>11</sup> 100-350 <sup>12</sup>	>20 <sup>13</sup> and adequate sources for recruitment	>20 but lacks recruitment to maintain	<20 and lacks recruitment
Percent Shade/Canopy Closure	-	-	-	-	-	40-55 <sup>15</sup> 50-65 <sup>16</sup> 60-75 <sup>17</sup> 80 <sup>18</sup>	-	-	-
Greenline Wetland Rating	54.0	60.1	56.1	50.0	-	-	-	-	-
Greenline Woody Cover	57.9	62.5	82.4	72.6	-	-	-	-	-
Physical Man-made Barriers <sup>19</sup>	-	-	-	-	-	-	Any in watershed allow passage @ all flows	Any don't allow passage @ base flows	Any don't allow passage @ range of flows
Off-channel Habitat & Refugia	-	-	-	-	-	-	Low energy backwaters & side channels	Some backwaters & high energy side channels	Few or no backwaters

Notes: 1) All PIBO data units converted from metric to English except for mm measurements; 2) Channels of <10 feet in width; 3) Channels of >10 to 20 feet in width; 4) Channels of >20 to 25 feet in width; 5) Channels of >25 to 50 feet in width; 6) Criteria is for wetted W/D ratio; 7) Criteria is for bankfull W/D ratio; 8) Fines defined as <0.85mm in gravel; 9) In non-forested systems with 2% or less gradient; 10) In Ponderosa

pine ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 11) In mixed conifer ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 12) In Lodgepole pine ecosystems (at least 6 inches in diameter and 10% > 12 inches in diameter; and at least 18 feet long or 1.5 times bankfull width); 13) LWD defined as >12 inch diameter and > 35 ft length; 14) Stream surveys conducted in 1995 and earlier a) included not only LW material within the bankfull channel, but also leaning trees that have the potential to fall into the stream, and b) included a "Brush" LWD category that is not considered functional LWD as per Amendment 29 DFCs and the MPI unless in Lodgepole Pine ecosystems. Stream surveys conducted in 1996 and later a) only included trees actually within the bankfull channel interacting with stream flow during bankfull conditions, and b) included a "Small" LWD category that is not considered functional LWD as described above; 15) In Ponderosa pine ecosystems; 16) In mixed conifer ecosystems; 17) In Lodgepole pine ecosystems; 18) In hardwood/meadow complexes; 19) Culvert barrier data from MNF Culvert Assessment GIS layer.

Table 15. Summary of Available R6 Stream Survey Data vs. Fish Habitat Standards for Streams within Allotments.

Thorn Creek

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	R6 Level II Stream Survey Data			Amend 29 DFC	NMFS Matrix of Pathways and Indicators Ranges of Criteria		
(Italics) Both (Bold & Italics)					Properly Functioning	At Risk	Not Properly Functioning
Stream Name	Thorn Creek Reaches 1- 2	Thorn Creek Reach 3	-	-	-	-	-
Pasture Name	Martin Corrals	Oregon Mine	-	-	-	-	-
Survey Date	1992 (July 3-7)	1992 (July 3-7)	-	-	-	-	-
Sample Type	-	-	-	ı	-	•	-
6 <sup>th</sup> Field HUC	170702010403	170702010403	-	-	-	-	-
Av Bankfull (B) and/or Wetted (W) Width (feet)	W 4.0	W 3.3	-	-	-	-	-
Av Gradient (%)	3.5	3.0	-	-	-	-	-
Av Residual Pool	0.5	0.6	-	-	-	-	-

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	DO Lavel III Of common Data		PAC FISH	Amend 29	NMFS Matrix of Pathways and Indicators Ranges of Criteria		
(Italics) Both (Bold & Italics)	R6 Level II Stream Survey Data			DFC	Properly Functioning	At Risk	Not Properly Functioning
Depth (feet)							
Pool Frequency (#/mi)	82.8	54.3	96 <sup>2</sup> 56 <sup>3</sup> 47 <sup>4</sup> 26 <sup>5</sup>	75-132 <sup>2</sup> 38-66 <sup>3</sup> 30-53 <sup>4</sup> 15-26 <sup>5</sup>	Meets pool freq & LWD recruitment standards channel width # pools/mile 5 feet 184 10 " 96 15 " 70 20 " 56 25 " 47 50 " 26	Meets pool freq standards but not LWD recruitment	Does not meet pool freq standards
Pool Quality	No >1m deep pools, Max spot temp 50.0F	No >1m deep pools, Max spot temp 54.0F	-	-	Pools >1m (3.28ft) deep, good cover, cool water, minimal filling	Few >1m pools or inadequate cover/temp, moderate filling	No >1m pools & inadequate cover/temp, major filling with sediment
Percent Pools	29.0	16.5	-	-	-	-	-
Bankfull (B) or Wetted (W) W/D Ratio	B 14.0	B 4.6	<10 <sup>6</sup>	<10 <sup>6</sup>	<10 <sup>7</sup>	10-12 <sup>7</sup>	>12 <sup>7</sup>
D50 (mm), or Dominant Substrate & Embeddedness	Cobble, Embeddedness >35%	Sand, Embeddedness < 35%	-	Embedded <=20%	Dominant substrate gravel (2-64 mm) or cobble (64-256 mm) (interstitial spaces clear), or embeddedness <20%	Gravel or cobble subdominant, or embeddedness 20-30% if dominant	Bedrock, sand, silt, or small gravel dominant, or embeddedness >30% if gravel or cobble dominant
Pct Fines <2 mm in Riffles (R) or Pool Tails (P)	-	-	-	-	<12% fines <sup>8</sup> in gravel	12-20% fines <sup>8</sup> in gravel	>20% fines <sup>8</sup> in gravel

PIBO Data <sup>1</sup> (Bold) R6 Survey Protocol	R6 Level II Stream Survey Data			Amend 29 DFC	NMFS Matrix of Pathways and Indicators Ranges of Criteria		
(Italics) Both (Bold & Italics)					Properly Functioning	At Risk	Not Properly Functioning
Percent Stable Banks (CS & FB)	96.3	100	>80	>90	>90% stable	80-90% stable	< 80% stable
Percent Stable Banks (CS, FB, US)	-	-	-	-	-	-	-
Percent Undercut Banks	-	-	>75	50-75% undercut <sup>9</sup>	-	-	-
Large Wood Frequency (#/mi) <sup>14</sup>	46.6 <sup>11</sup> , Poor Recruitment	24.8 <sup>11</sup> , Poor Recruitment	>20 <sup>13</sup>	20-70 <sup>10</sup> 80-120 <sup>11</sup> 100-350 <sup>12</sup>	>20 <sup>13</sup> and adequate sources for recruitment	>20 but lacks recruitment to maintain	<20 and lacks recruitment
Percent Shade/Canopy Closure	>60	>60	-	40-55 <sup>15</sup> 50-65 <sup>16</sup> 60-75 <sup>17</sup> 80 <sup>18</sup>	-	-	-
Greenline Wetland Rating	-	-	-	-	-	-	-
Greenline Woody Cover	-	-	-	-	-	-	-
Physical Man-made Barriers <sup>19</sup>	1 barrier culvert	7 culvert barriers	-	-	Any in watershed allow passage @ all flows	Any don't allow passage @ base flows	Any don't allow passage @ range of flows
Off-channel Habitat & Refugia	Side channels on 6% of reaches	Side channels on 2.4% of reaches	-	-	Low energy backwaters & side channels	Some backwaters & high energy side channels	Few or no backwaters

Notes: 1) All PIBO data units converted from metric to English except for mm measurements; 2) Channels of <10 feet in width; 3) Channels of >10 to 20 feet in width; 4) Channels of >20 to 25 feet in width; 5) Channels of >25 to 50 feet in width; 6) Criteria is for wetted W/D ratio; 7) Criteria is for bankfull W/D ratio; 8) Fines defined as <0.85mm in gravel; 9) In non-forested systems with 2% or less gradient; 10) In Ponderosa

pine ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 11) In mixed conifer ecosystems (at least 12 inches in diameter and 20% > 20 inches in diameter; and at least 35 feet long or 1.5 times bankfull width); 12) In Lodgepole pine ecosystems (at least 6 inches in diameter and 10% > 12 inches in diameter; and at least 18 feet long or 1.5 times bankfull width); 13) LWD defined as >12 inch diameter and > 35 ft length; 14) Stream surveys conducted in 1995 and earlier a) included not only LW material within the bankfull channel, but also leaning trees that have the potential to fall into the stream, and b) included a "Brush" LWD category that is not considered functional LWD as per Amendment 29 DFCs and the MPI unless in Lodgepole Pine ecosystems. Stream surveys conducted in 1996 and later a) only included trees actually within the bankfull channel interacting with stream flow during bankfull conditions, and b) included a "Small" LWD category that is not considered functional LWD as described above; 15) In Ponderosa pine ecosystems; 16) In mixed conifer ecosystems; 17) In Lodgepole pine ecosystems; 18) In hardwood/meadow complexes; 19) Culvert barrier data from MNF Culvert Assessment GIS layer.